

SPEC No. Rev. No. Pages PACKAGE OUTLINE SPECIFICATION НТС-РО-ТО92-ТА 1/1 А Package Name TO-92 (Tape) т F1 P1 Package Symbol Values & Tolerance Items Outline Body width  $4.5 \pm 0.1$ A1 Dimension Body height  $4.5 \pm 0.1$ А т  $3.5 \pm 0.1$ Body thickness Lead wire diameter d  $0.38 \pm 0.02$ Pitch of component Ρ  $12.7 \pm 0.3$ Feed hole pitch P0  $12.7 \pm 0.2$ Hole center to component center Ρ2 6.35 ± 0.3 Lead to lead distance F1, F2  $2.5 \pm 0.3$ Component alignment, F-R Δh  $0 \pm 1.0$ Type width W 18.0 + 1.0, - 0.5 Hole down tape width W0  $6.0 \pm 0.5$ W1 Hole position  $9.0 \pm 0.5$ Hole down tape position W2 1.0 MAX Height of component from tape center Н 19.0 + 2.0, -0Lead wire clinch height HO 16.0 ± 0.5 Lead wire (tape portion) L1 2.5 MIN Feed hole diameter D0  $4.0 \pm 0.2$ **Taped Lead Thickness** t1  $0.4 \pm 0.05$ **Carrier Tape Thickness** t2  $0.2 \pm 0.05$ Position of hole Ρ1  $3.85 \pm 0.3$ ΔР Component alignment  $0 \pm 1.0$ 1. Dimensions are in millimeters. 2. Dimensions are inclusive of plating. Note 3. Dimensions are exclusive of mold flash (or protrusion) and metal burr.