

RoHS COMPLIANT

REV	ECN NO.	DESCRIPTION	DATE
A		RELEASE	JAN. 06'04
B		ADD. RoHS	OCT. 15'07
C		MODIFY P/N	APR. 28'11

■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 7A AC/DC
- Withstanding Voltage : 1500V AC/minute
- Insulation Resistance : 1000M Ω min
- Temperature Range : - 25 $^{\circ}$ C to + 85 $^{\circ}$ C
- Contact Resistance : 20m Ω max

■ WAFER

- Poles : 2~15
- Material : Contact : Brass, Tin Plated
Base : Nylon 66 UL94V-0
- Q' ty: 1000 pcs./Bag

Poles	Dimension(mm)	
	A	B
2	3.96	7.86
3	7.92	11.82
4	11.88	15.78
5	15.84	19.74
6	19.80	23.70
7	23.76	27.66
8	27.72	31.62
9	31.68	35.58
10	35.64	39.54
11	39.60	43.50
12	43.56	47.46
13	47.52	51.42
14	51.48	55.38
15	55.44	59.34

TOLERANCE UNLESS
OTHERWISE SPECIFIED

LINEAR		ANGLE	
X.	$\pm$	X $^{\circ}$	$\pm$
.X	$\pm$ 0.30	.X $^{\circ}$	$\pm$
.XX	$\pm$ 0.20	.XX $^{\circ}$	$\pm$
.XXX	$\pm$	.XXX $^{\circ}$	$\pm$
APPD			
CHKD			
DRAW	Z	APR. 28'2011	

PROJECTION



UNITS

MM

SCALE

SIZE

A4



GOLD-TEK ELECTRIC CO., LTD.

TITLE

PITCH: 3.96mm

WAFER CONN.

CPART NO.

PART NO.

1120**RT

CAD NO. 1056

F:\PDF\HW\HW-A0042

SHEET

1 OF 1

圖面編號:GTKSD1363-C(1)