

2.54±0.10

2.54*No. Of Contacts±0.50

2.54*(No. Of Contacts-1)±0.30

2.54±0.10

SQ 0.64±0.02

2.54±0.10

16.0

3.00

2.54*(No. of Contacts-1)±0.10

2.54±0.05

ø1.02±0.05

PCB Layout

Specifications:

Current rating: 3A AC/DC

Contact Resistance: 20m ohm Max

Insulation Resistance: 1000M ohm Min

Withstanding Voltage: 500V AC For one Minute

Operating Temperature Range: -40°C To +85°C

Materials:

Insulator: High Temperature Plastic(UL94V-0)

Standard Color: Black

Contact: Copper Alloy

Plating: Gold/Matte Tin/Selective Gold Plated

How To Order

2211S-XXX-070-F2

G:Gold Plated

MT:Matte Tin Plated

SG:Gold Plated On Contact Area,
Matte Tin Plated On Solder Tail.

No. Of Contacts

Straight Type

1

2

3

4

5

A

B

C

RoHS Compliant

F				DRAWN: Jamie Chuang	GENERAL TOLERANCE: .X=±0.30 .XX=±0.20	Neltron Connectors Neltron Industrial Co., Ltd.		SIZE A4	D		
E											
D				CHECKED: Jerry Chen	UNIT: MM	DESCRIPTION: 2.54mm Pin Header Single Row Straight Type					
C					SCALE: 1:1						
B				APPROVAL: Rory Chen	SHEET: 1/1	PART NO: 2211S-XXX-070-F2					
A	26-FEB-2024	(PC0643)	Jamie		PROJECTION:						
REV	DATE	FILE	BY								