

1		2		3	4	5
					Specifications: Current Rating:3.0A AC/DC Voltage Rating:250V AC/DC Contact Resistance:20m ohm.Max. Insulation Resistance:1000M ohm.Min. Withstanding Voltage:600V AC/Minute Operating Temperature Range:-40°C To +105°C	A
					Material and Finish: Insulator:Thermoplastic (UL94V-0) Insulator Color:Black Contact:Copper Alloy Plating:Gold/Tin/Selective Gold Plated Max Reflow Temperature: 260°C for 5 SEC	B
					How To Order 2213S-XXX-BK-F2 Black G:Gold Plated T:Tin Plated SG:Selective Gold Plated SG10:10u" Gold Plated On Contact Area, Tin On Solder Tail SG30:30u" Gold Plated On Contact Area, Tin On Solder Tail No. Of Contacts Straight Type	
					2.54X(No. Of Contacts/2)±0.50 2.54X(No. Of Contacts/2-1)±0.30 2.54±0.10 0.64±0.02 SQ 5.08 2.54±0.10 2.54 11.54±0.2 3.0 2.54X(No of Contacts/2-1)±0.10 2.54±0.05 Ø1.02±0.05 2.54±0.05 PCB Layout	C
					RoHS Compliant	D
F				DRAWN:	GENERAL TOLERANCE:	
E				Lisy Liu	.X=±0.20	
D				CHECKED:	.XX=±0.15	
C				Jerry Chen	UNIT: MM	
B				APPROVAL:	SCALE: 1:1	
A	23-AUG-2022		Lisy		SHEET: 1/1	
REV	DATE	FILE	BY	Rory Chen	PROJECTION:	
					Neltron Industrial Co., Ltd.	
					DESCRIPTION:	SIZE
					2.54mm Pin Header Double Row Straight Type	A4
					PART NO:	
					2213S-XXX-BK-F2	