

1		2		3		4		5																																											
		Dim.A=2.54XNo. of Contacts/2+19.5±0.35 Dim.B=2.54X(No. of Contacts/2-1) 2.54±0.05 SQ0.64±0.01 Pin 2 Pin 1 8.30				Specifications Current Rating: 3.0A AC/DC Voltage Rating: 250V AC/DC Contact Resistance: 20m ohm. Max Insulation Resistance: 1000M ohm. Min Withstanding Voltage: 600V AC For one minute Operating Temperature Range : -40°C to +105°C				A																																									
4.30 7.60 Neltron Short Ejector		7.95 10.80 Key Neltron Long Ejector		17.00 2.54 3.40±0.20		How To Order 2216R-XXG-XX-XX-H-X-F5 Blank Without Neltron Logo P:With Neltron Logo Standard Color:Black GR:Grey 01:Short Ejector 02:Long Ejector 02B:Long Ejector(B Type) G:Gold Plated No. Of Contacts Right Angle		B																																											
		8.05 10.80 Key Neltron Long Ejector(B Type)		2.54±0.05 2.54±0.05 Ø1.02±0.05 P.C.B Layout		RoHS Compliant		C																																											
<table><tr><td>No. of Contacts</td><td>Dim.A</td><td>Dim.B</td><td>No. of Contacts</td><td>Dim.A</td><td>Dim.B</td></tr><tr><td>6</td><td>27.12</td><td>5.08</td><td>20</td><td>44.90</td><td>22.86</td></tr><tr><td>8</td><td>29.66</td><td>7.62</td><td>24</td><td>49.98</td><td>27.94</td></tr><tr><td>10</td><td>32.20</td><td>10.16</td><td>26</td><td>52.52</td><td>30.48</td></tr><tr><td>12</td><td>34.74</td><td>12.70</td><td>30</td><td>57.60</td><td>35.56</td></tr><tr><td>14</td><td>37.28</td><td>15.24</td><td>34</td><td>62.68</td><td>40.64</td></tr><tr><td>16</td><td>39.82</td><td>17.78</td><td>40</td><td>70.30</td><td>48.26</td></tr></table>		No. of Contacts	Dim.A	Dim.B	No. of Contacts	Dim.A	Dim.B	6	27.12	5.08	20	44.90	22.86	8	29.66	7.62	24	49.98	27.94	10	32.20	10.16	26	52.52	30.48	12	34.74	12.70	30	57.60	35.56	14	37.28	15.24	34	62.68	40.64	16	39.82	17.78	40	70.30	48.26								
No. of Contacts	Dim.A	Dim.B	No. of Contacts	Dim.A	Dim.B																																														
6	27.12	5.08	20	44.90	22.86																																														
8	29.66	7.62	24	49.98	27.94																																														
10	32.20	10.16	26	52.52	30.48																																														
12	34.74	12.70	30	57.60	35.56																																														
14	37.28	15.24	34	62.68	40.64																																														
16	39.82	17.78	40	70.30	48.26																																														
F				DRAWN: Lisy Liu	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15		Neltron Connectors Neltron Industrial Co., Ltd.				SIZE A4																																								
E																																																			
D				CHECKED: Jerry Chen	UNIT: MM SCALE: 1:1		DESCRIPTION: 2.54mm Shrouded Header With Ejector Right Angle Type																																												
C																																																			
B				APPROVAL: Rory Chen	SHEET: 1/1 PROJECTION:		PART NO: 2216R-XXG-XX-XX-H-X-F5																																												
A	29-Aug-2023	(P0001)	Lisy Liu																																																
REV	DATE	FILE	BY									D																																							