

Specifications:
Current Rating: 3.0A AC,DC
Voltage Rating: 250V AC,DC
Contact Resisitance: 10m ohm.Max
Insulation Resisitance: 1000M ohm.Min
Withstanding Voltage: 800V AC/Minute
Operating Temperature Range: −25°C ~ +85°C

Material And Finish:
Insulator: Nylon 66 (UL94V−0)

How To Order
2318HJ−XX
No. Of Contacts
Housing



B

Pin.No	Dim.A	Dim.B	Pin.NO	Dim.A	Dim.B
2	2.50	5.70	10	22.50	25.70
3	5.00	8.20	11	25.00	28.20
4	7.50	10.70	12	27.50	30.70
5	10.00	13.20	13	30.00	33.20
6	12.50	15.70	14	32.50	35.70
7	15.00	18.20	15	35.00	38.20
8	17.50	20.70	16	37.50	40.70
9	20.00	23.20	20	47.50	50.70

RoHS Compliant

REV	DATE	FILE	BY
F			
E			
D			
C	01−JUL−2022	Update Drawing	BEN
B	20−JAN−2022	Update DWG	MEI
A	01−SEP−2014	(P0257)	EISEN

DRAWN: EISEN
CHECKED: DENNIS
APPROVAL: MIKE

GENERAL TOLERANCE:
.X=±0.30
.XX=±0.20

UNIT: MM
SCALE: 1:1
SHEET: 1/1
PROJECTION:

Neltron Connectors **Neltron Industrial Co., Ltd.**

DESCRIPTION: 2.50mm Wire To Board Housing

PART NO: 2318HJ−XX

SIZE **A4**