





公差/General tolerances (mm)													D
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2



Note:
The A&Z(H) in the name means: A(H) and Z(H).

2	Pin	Copper	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)		300V/15	/	300/10
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	II/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)		/	320/20	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		/	4	/
间距/Pitch(mm)/线数范围/Poles		5.0/N=02~24P		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

MATERIAL:		SURFACE/COLOR:	
MAT NO./REV: - / 00		MAT STATUS: 批量	
APPD: 兰泰华		NAME:	
CHKD: 黄耀志		2EDGV-5.0-XXP-1Y-00A&Z(H)	
DRFT: 方哲盛		DRAWING NO.	
2022.07.29		200100381	
REV		TYPE	
ECN		CUSTOMER DRAWING	
DESCRIPTION		DRAWING STATUS	
DRFT		已发布	
DATE		SCALE	
A3		5:1	
(Inch)		SHEET	
		1/1	