


Specifications:
Current rating:1.0A AC,DC
Voltage rating:250V AC, DC
Contact tesistance:20m ohm Max
Insulation resistance:1,000M ohm Min
Withstanding voltage:500V AC/minute
Operating Temperature:-40°C ~ +105°C




Material:
Insulator:PBT UL94V-0
Color:Black
Coctact:Copper Alloy
Plating:Selective Gold Plated

How To Order
4400-XXSR-XX-XX-XX
Blank:Without Logo
P:With"Neltron" Logo
Blank:Black
BU:Blue GR:Gray
Blank:Without Nose
CK:With Nose
SR:With Strain Relief
No. Of Positions

CIRCUITS	DIM.A	DIM.B	DIM.C	CIRCUITS	DIM.A	DIM.B	DIM.C
10	15.20	8.00	9.00	36	41.20	34.00	35.00
12	17.20	10.00	11.00	38	43.20	36.00	37.00
14	19.20	12.00	13.00	40	45.20	38.00	39.00
16	21.20	14.00	15.00	44	49.20	42.00	43.00
18	23.20	16.00	17.00	48	53.20	46.00	47.00
20	25.20	18.00	19.00	50	55.20	48.00	49.00
22	27.20	20.00	21.00	54	59.20	52.00	53.00
24	29.20	22.00	23.00	56	61.20	54.00	55.00
26	31.20	24.00	25.00	60	65.20	58.00	59.00
28	33.20	26.00	27.00	62	67.20	60.00	61.00
30	35.20	28.00	29.00	64	69.20	62.00	63.00
32	37.20	30.00	31.00	68	73.20	66.00	67.00
34	39.20	32.00	33.00				

RoHS Compliant

F				DRAWN: JERRY	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15	 Neltron Industrial Co., Ltd.	
E							
D				CHECKED:	UNIT: MM SCALE: 1:1	DESCRIPTION: 2.0mm IDC Socket With Strain Relief	
C							
B	01-DEC-2020	Modify Part No	LISY	APPROVAL:	SHEET: 1/1	PART NO: 4400-XXSR-XX-XX-XX 	
A	30-JAN-2020	(P0001)	JERRY				
REV	DATE	FILE	BY	RORY	PROJECTION: 		

A4