




Dimension:

Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B
2	5.08	2.54	12	30.48	27.94	22	55.88	53.34	32	81.28	78.74
3	7.62	5.08	13	33.02	30.48	23	58.42	55.88	33	83.82	81.28
4	10.16	7.62	14	35.56	33.02	24	60.96	58.42	34	86.36	83.82
5	12.70	10.16	15	38.10	35.56	25	63.50	60.96	35	88.90	86.36
6	15.24	12.70	16	40.64	38.10	26	66.04	63.50	36	91.44	88.90
7	17.78	15.24	17	43.18	40.64	27	68.58	66.04	37	93.98	91.44
8	20.32	17.78	18	45.72	43.18	28	71.12	68.58	38	96.52	93.98
9	22.86	20.32	19	48.26	45.72	29	73.66	71.12	39	99.06	96.52
10	25.40	22.86	20	50.80	48.26	30	76.20	73.66	40	101.60	99.06
11	27.94	25.40	21	53.34	50.80	31	78.74	76.20			

Specifications:

Current rating:3.0A AC/DC

Voltage rating:100V AC/DC

Contact resistance:20m ohm. max.

Insulator resistance:1000M ohm. Min.

Withstanding voltage:1000V AC for one minute

Operating temperature range:-40°C to +105°C

Material and Finish:

Insulator:High Temp. Plastic(PPS UL94V-0)

Standard Color:Black

Contact:Beryllium Copper(Becu) Gold Plated

Sleeve Barrel:Brass Tin Plated


How To Order

6604S-XX



No. of Positions

Socket Single Row



PCB Layout

RoHS Compliant

				DRAWN: P.D.J	GENERAL TOLERANCE: X.X=±0.2 X.XX=±0.15	Neltron Industrial Co., Ltd.	DESCRIPTION: 2.54mm Machine Pin Socket Single Row	SIZE A4
E				CHECKED: Jeremy Liu	UNIT: MM			
D				APPROVAL: Mike Wu	SCALE:	PART NO: 6604S-XX		
C	07-Aug-2015	ECN-TW1508002	Miller Yu		SHEET: 1 / 1			
B	23-Feb-2011	ECN-CN1102006	Richie		PROJECTION:			
A	04-Mar-2008		P.D.J					
REV	DATE	FILE	BY					