

**TECHNICAL DATA**

# Fluke AC280 SureGrip™ Hook Clips



## Key features

- One pair of nickel-plated clips (red, black) with a profile narrowing to 5.6 mm at the tip and a hook opening of 6.4 mm at the front, reducing to 2 mm at the base
- Provides reliable and secure connections for precise electrical measurements
- Rated CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 3 A
- Recommended for use with TL222 and TL224 test leads

## Product overview: Fluke AC280 SureGrip™ Hook Clips

SureGrip™ accessories are designed to improve steadiness in slippery hands. Rubber overmolded surfaces and finger-hugging curves give the user a comfortable, reliable grip on the accessory so they can focus on making an accurate measurement.

## Ordering information



### **Fluke AC280**

Fluke AC280 SureGrip™ Hook Clips

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Europe/M-East/Africa  
+31 (0)40 267 5100  
In Canada (800)-36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com/en-th](http://www.fluke.com/en-th)

©2025 Fluke Corporation. Specifications subject to  
change without notice.  
04/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**