## AT8502D

## 2 In 1 Hot Air Rework Station



## Features:

- Hot air station and soldering station 2 in 1 design, saving working space.
- Hot air station: 550W, rapid heating and high efficiency.
- Soldering station: 50W, rapid heating and temperature recovery.
- LCD display, support display accurate temperature & airflow.
- Diaphragm pump with high pressure make it suitable for various nozzles.
- 3 set shortcut air volume/temperature to simplify operations.
- Support °C and °F switchable.
- Support standby and temp calibration function.
- Intelligent cooling system and deferred power-off function.
- Cold air function to cool components.

## Specification:

Item No	AT-8502D	
Voltage	AC(100V/110V/120VII220V/230V/240) 50/60Hz	
Total Power	700W	
Name	Soldering station	Hot air station
Power	50W	550W
Temperature range	200°C~480°C/392~896°F	100°C~500°C/212~932°F
Pump		Diaphragm
Air flow		23L/min
The handle type	AP-50	AP-551B
Soldering tip	Т900-В	
Noise		<50dB(A)
Package list	Main Unit: 1 unit Hot Air Gun: 1 PCS Gun Holder: 1 PCS AC Cord: 1 PCS	Manual: 1 PCS Iron Handle Set: 1 PCS Nozzle: 4 PCS Iron Stand: 1 PCS
Standard packing	Inner box: 354x329x194(mm)  N.W.: 4.85kg  G.W.: 5.41kg  Carton: 4PCS/carton  Size: 670x370x415(mm)  N.W.: 21.64kg  G.W.: 22.85kg	
Applications	<ul> <li>Thermoplastic soldering</li> <li>Education and practice</li> <li>On-site soldering for PVC/PE/PP/PVDF etc.</li> <li>Maintenance</li> </ul>	