AT-937/AT-937A/AT-989



ESD Safe Constant Temperature Controllable Soldering Station



Features:

- MCU controlled temperature calibration with PID system equipped.
- The heater using low voltage AC source to ensure the antistatic and no leakage, no interference.
- Steady temperature setting with 200 \sim 480 $^{\circ}$ C.
- Legerity handle suitable for long time operation.
- Unique temperature locks setting to avoid adjusting temperature.



Specification:

Item No	AT-937	AT-937A	AT-989
Voltage	AC(100V/110V/120V 220V/230V/240) 50/60Hz		
Power	50W	65W	65W
Temperature range	200°C∼480°C	200°C∼480°C	200°C∼480°C
Temperature Stability	±2°C(in still air,no load)	±2°C(in still air,no load)	±2°C(in still air, no load)
The handle type	AP-50	AP-65	AP-65A
Soldering tip type	Т900-В	Т900-В	Т900-В
Heat	Four core stainless steel heater	Pluggable Four core stainless steel heater	High quality four-core wire heater
Package list	Main unit: 1unit Iron stand: 1 PCS Manual: 1 PCS Handle set : 1 PCS AC cord: 1 PCS Cleaning sponge: 1 PCS		
Standard Packing	Inner box: 26.5x23x16(cm) N.W.: 1.6kg G.W.: 1.78kg Carton: 12PCS/Carton Size: 55x48x50.5(cm) N.W.: 19.2kg G.W.: 21.4kg		
Applicable	Production lineEducation and practice		Enterprises Hobby

Note: T900 series soldering tip details in page 24.