



C707A SIMLOCK® 2.5 mm with wide solder tails

Part No. C707 10M006 512 2

- Small overall dimension
- With wide solder tails for overhead soldering
- Secure card position
- Reliable contact of SIM-Card pads
- Easy and safe locking
- SMT solderable
- Packed in tape & reel
- Pick & place capable



View represents all available contact positions.

For more information, please contact us [here](#).

Series Mobile Connectors

Subseries Mobile Connectors C707A

COMMON CHARACTERISTICS		
No. of contacts		6
Contact position		GSM
Function		Chip card reader
Style		SIMLOCK
ELECTRICAL CHARACTERISTICS		
Contact resistance	IEC 60512-2, Test 2a	max. 100 mΩ
Insulation resistance	IEC 60512-3, Test 3a	max. 1 GΩ
Voltage proof	IEC 60512-2, Test 4a	125 V
Rated voltage	DIN EN 60664-1 / IEC 60664-1	max. 15 VDC
Rated current at 40°C		max. 1 A
CLIMATICAL CHARACTERISTICS		
Operating temperature		-25 °C to +85 °C
MECHANICAL CHARACTERISTICS		
Mechanical lifetime		1.500 mating cycles
Contact force		min. 0.20 N
MATERIALS		
Contacts		Copper alloy
Insulator		High temperature thermoplastic
Cover		High temperature thermoplastic
Plating contacts		min. 0.8 μm Au
Plating solder area		min. 4 μm Sn
Underlayer		min. 2 μm Ni

Warranties, Liability The information on this data sheet is provided "e:as is"e; and without warranty of merchantability or fitness for any particular purpose. While the information provided is believed to be accurate, it may include errors or inaccuracies. In no event shall Amphenol-Tuchel Electronics GmbH be liable for any special, indirect or consequential damages relating to this material, unless caused by gross negligence or law infringement. We reserve the right to change the design due to improvement in quality, development or production requirements. Copyrights © Copyright Amphenol-Tuchel Electronics GmbH, Heilbronn, Germany. All rights reserved. Amphenol-Tuchel Electronic GmbH retains copyright in the entire text and graphic content of this data sheet. Modification, distribution, reposting or making available on another server any of our web content without the written permission of Amphenol-Tuchel is not allowed. Amphenol-Tuchel Electronics GmbH • August-Haessler-Str. 10 • 74080 Heilbronn • Germany • Phone +49 7131 929-0 • Fax +49 7131 929-486 • info@amphenol.de • www.amphenol.info