Shenzhen Skyworth Lighting Electric Co.,Ltd

LED Tube Light Specification

Version: Q/SKY-RG-7046

	Type	LED lighting p	roducts	Code No.	67-GG0000406-(WW/NW/CW)
	Product	T8 tube with internal driver (0.6m milky cover)		Model No.	CGG-8729 (WW/NW/CW)
A	pplication	Building, Hotel, Meeting Room,		Std & AUT	CE / ROHS
	Type	Item			Parameter
P a r a m e t e r	Basic Parameter	LED Type and Qty		Epistar 2835 Chip	
		Input Voltage/Frequency Range		AC100V-240V 50/60HZ	
		Main Material		Plastic	
		Appearance		Milky White	
		Holder		G13	
		IP Code		IP20	
	Electric Parameter	Color Temperature		2200-3500K / 3700-5000K / 5300-7000K	
		Total Power		9W	
		Efficacy		$100LM/W \pm 10\%$	
		Power efficiency		85%	
		Power factor		>0.95	
		CRI		>80	
		Other		Built-in non-isolated power supply, light uniformity, no dark side of the area, vibration-free weld, PC cover squeeze no sound	
	Other Parameter	Beam Angle		140°	
		Insulation class		II	
		Installation		G13	
		Product Size (mm)		¢ 26*588	
		Carton Size (mm)		660*215*220 (25PCS/Ctn)	
		Packaging style		EPE + Carton + Stickers	
		Product Weight		120g	
		Operating Environment		T: -20°C to 40°C; H: 20%RH to 90%RH	
		Other		30,000 Hrs	
	Product dimension		Wirin	g Diagram Product picture	
- - - - -	588		AC:	100-240V———— N	

Made by: Audited by: Approved by:	
-----------------------------------	--