## Shenzhen Skyworth Lighting Electric Co.,Ltd

				Code No.	Version: Q/SKY-RG-7046
Туре		LED lighting p	LED lighting products		67-GG0000407-WW/NW/CW)
Product		T8 tube with internal driver (1.2m milky cover)		Model No.	CGG-8749 (WW/NW/CW)
Application:		Building, Hotel, Meeting Room, Bus		Std & AUT	CE / ROHS
Pa	Туре	Item		Parameter	
	Basic Parameter	LED Type and Qty		Epistar 2835 Chip	
		Input Voltage/Frequency Range		AC100V-240V 50/60HZ	
		Main Material		Plastic	
		Appearance		Milky White	
		Holder		G13	
		IP Code		IP20	
	Electric Parameter	Color Temperature		2200-3500K / 3700-5000K / 5300-7000K	
		Total Power		18W	
		Efficacy		$100LM/W \pm 10\%$	
		Power efficiency		90%	
r a		Power factor		>0.95	
m u		CRI		>80	
e t e		Other		Built-in non-isolated power supply, light uniformity, no dark side of the area, vibration-free weld, PC cover squeeze no sound	
r	The Other Parameter	Beam Angle		140°	
		Insulation class		Ш	
		Installation		G13	
		Product Size (mm)		¢ 26*1198	
		Carton Size (mm)		1265*225*225 (25PCS/Ctn)	
		Packaging style		EPE + Carton + Stickers	
		Product Weight		210g	
		Operating Environment		T: -20°C to 40°C; H: 20%RH to 90%RH	
		Other		30,000 Hrs	
Product dimension Wiring			Wiring	Diagram	Product picture
			L L	N0-240VΝ	) anno
Aade	e by :	Audite	Audited by:		Approved by:

LED Tube Light Specification