



Power Rating at 70°C	Max. Working Voltage	Max. Overload Voltage	Operating Temp. (°C)	Tolerance %	Resistance Range	Standard Series	Dimension (mm)				
							L	W	H	t1	t2
1/16W	25V	50V	-55~+125	Jumper ±1 ±2 ±5	<50mΩ 100Ω-1MΩ 2Ω-3.3MΩ 2Ω-3.3MΩ	E-96 E-24 E-24	1.00±0.10	0.50±0.05	0.35±0.05	0.20±0.10	0.25±0.10
1/10W (1/16W)	50V	100V	-55~+125	Jumper ±1 ±2 ±5	<50mΩ 10Ω-1MΩ 10Ω-1MΩ 1Ω-10MΩ	E-96 E-24 E-24	1.60±0.10	+0.15 0.80 -0.10	0.45±0.10	0.30±0.20	0.30±0.20
1/8W (1/10W)	150V	300V	-55~+125	Jumper ±1 ±2 ±5	<50mΩ 10Ω-1MΩ 10Ω-1MΩ 1Ω-10MΩ	E-96 E-24 E-24	2.00±0.15	+0.15 1.25 -0.10	0.55±0.10	0.40±0.20	0.40±0.20
1/4W (1/8W)	200V	400V	-55~+125	Jumper ±1 ±2 ±5	<50mΩ 10Ω-1MΩ 10Ω-1MΩ 1Ω-10MΩ	E-96 E-24 E-24	3.10±0.15	+0.15 1.55 -0.10	0.55±0.10	0.45±0.20	0.45±0.20
1/3W (1/4W)	200V	400V	-55~+125	Jumper ±1 ±2 ±5	<50mΩ 10Ω-1MΩ 1Ω-10MΩ 1Ω-10MΩ	E-96 E-24 E-24	3.10±0.10	2.60±0.15	0.55±0.10	0.50±0.25	0.50±0.20
3/4W (1/2W)	200V	400V	-55~+125	Jumper ±1 ±2 ±5	<50mΩ 10Ω-1MΩ 1Ω-10MΩ 1Ω-10MΩ	E-96 E-24 E-24	5.00±0.10	2.50±0.15	0.55±0.10	0.60±0.25	0.50±0.20
1W	200V	400V	-55~+125	Jumper ±1 ±2 ±5	<50mΩ 10Ω-1MΩ 1Ω-10MΩ 1Ω-10MΩ	E-96 E-24 E-24	6.35±0.10	3.20±0.15	0.55±0.10	0.60±0.25	0.50±0.20