



Openframe Infrared(IR) Touch Monitor--E Series

17"Openframe IR Touch Monitor suraface waterproof can meet IP65 standard
With 3mm tempered glass support Vandalproof
Have a beautiful appearance with plastic and metal case
With AUO new Brandgrade A TFT LCD panel
(250cd/m2 brightness ,1280X1024 resolution , 80°/85° view angle)

- Features
- Specifications
- Part Numbers
- Download

General	
Model	COT170E-IWF02
Series	Waterproof and Compact
Monitor Dimensions	Width: 368mm Height: 306mm Depth: 49.5mm
LCD Type	17" SXGA Color TFT-LCD
Video Input	VGA and DVI
OSD controls	Allow on-screen adjustments of Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset
Power Supply	Type: External brick Input (line) voltage: 100-240 VAC, 50-60 Hz Output voltage/current: 12 volts at 4 amps max
Mount Interface	1)VESA 75mm and 100mm 2)Mount bracket, horizontal or vertical
LCD Specification	
Active Area(mm)	337.920(H)×270.336(V)
Resolution	1280×1024@75Hz
Dot Pitch(mm)	0.264×0.264
Nominal Input Voltage VDD	+5.0V(Typ)
Viewing angle (v/h)	85°/80°
Contrast	1000:1
Luminance(cd/m2)	250
Response Time(Rising/Falling)	5s/5s
Support Color	16.7M colors
Backlight MTBF(hr)	30000
Touchscreen Specification	
Type	Cjtouch Infrared IR touch screen Dual touch
Resolution	4096*4096
Light Transmission	92%
Touch Life Cycle	50 millions
Touch Response time	16ms
Touch System Interface	USB interface
Power consumption	+5V@80mA
External AC Power Adapter	
Output	DC 12V /4A
Input	100-240 VAC, 50-60 Hz
MTBF	50000 hr at 25°C
Environment	
Operating Temp.	0 ~ 50°C
Storage Temp.	-20 ~ 60°C
Operating RH:	20% ~ 80%
Storage RH:	10% ~ 90%

Block B,3th floor,building 6,Anjia industrial park,WuLian,FengGang,DongGuan,China
+86-769-33231050 +86-769-82522516
+86-769-82522517
cjtouch@cjtouch.com

CE | FC | ISO 14001 | RoHS | ISO 9001

Touch from start

