

MATERIAL:		SURFACE/COLOR:			
MAT NO./REV: 11020000046-1 / 00		MAT STATUS: 批量			
NAME					
DC4-PE-01P-1C-00Z (H)					
DRAWING NO. 200309000		TYPE CUSTOMER DRAWING		DRAWING STATUS work	SHEET 2:1 1/1

未注公差/General tolerances (mm)														 0.1/10 
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2°
UL 标准/ UL Standard:										B	C	D		
额定电压/ 电流/ Rated Voltage(V)/ Current(A)										/	/	/		
IEC 标准/ IEC Standard:														
过压类别/ Overvoltage Category/ 污染等级/ Pollution Degree										III/ 3	III/ 2	II/ 2		
额定电压/ 电流/ Rated Voltage(V)/ Current(A)										/	/	/		
额定脉冲电压(KV)/ Rate Impulse Voltage(KV)										8.0	/	/		
螺丝扭矩/ Torque Tightening(N m/ Lb.in)										MB, 0.66/ 6.0				
线径范围(硬线和软线)/ Wire Range(rigid and flexible)(AWG mm²)										22~10 / 0.5~4				
间距/ Pitch(mm)/ 线数范围/ Poles										6.10/ 01P				
剥线长度/ Stripping length(mm)										8~9				
使用温度范围/ Operating temperature(°C)										- 40~+105				
符合 RoHS环保要求/ Conform to RoHS										Yes				
标准颜色编号/ Standard color number: PANTONE / RAL										/				