




DEGSON ELECTRONICS CO., LTD.

Product Specification



DG66S-B



"S"=11.11x(P-1)
"L"=11.11x(P-1)+12.4

Materials

Housing: PA66,UL94V-0
Terminal: Brass,0.8t,Tin-Plated
Screw: Steel,M4 Ni-Plated

Capability

Rated: 300V / 30A
Temp.Range: -40°C~+105°C
Withstand Voltage: AC2000V / 1Min
Insulation Resistance: 500MΩ / DC500V
Wire Range: 22-10AWG
Max.Torque Value: 1.2N.m 10.6Lb.in

HOW TO ORDER:

DG66S-B — **P** — —

X	X	X
Customer Request		

Series No. No. of Pole

Color

1 Gray	5 Orange	9 White
2 Blue	6 Red	
3 Black	7 Trans- parent	
4 Green	8 Yellow	

Poles	2	3	4	5	6	7	8	9	10	11	12	13	14	15
L(mm)	23.51	34.62	45.73	56.84	67.95	79.06	90.17	101.28	112.39	123.50	134.61	145.72	156.83	167.94
S(mm)	11.11	22.22	33.33	44.44	55.55	66.66	77.77	88.88	99.99	111.10	122.21	133.32	144.43	155.54
Poles	16	17	18	19	20	21	22	23	24	25	26	27	28	
L(mm)	179.05	190.16	201.27	212.38	223.49	234.60	245.71	256.82	267.93	279.04	290.15			
S(mm)	166.65	177.76	188.87	199.98	211.09	222.20	233.31	244.42	255.53	266.64	277.75			



DEGSON ELECTRONICS CO.,LTD.

NAME

DG66S-B