

DLC Display Co., Limited

德爾西顯示器有限公司



MODEL No: DLC1010EZK-T-5

TEL: 86-755-86029824

FAX: 86-755-86029827

E-MAIL: sales@dlcdisplay.com

WEB: www.dlcdisplay.com

1. Scope

This data sheet is to introduce the specification of DLC1010EZK-T-5 active matrix TFT module. It is composed of a color TFT-LCD panel, driver ICs, FPC, backlight unit and a resistive touch panel. The 10.1" display area contains 1024(RGB) x 600 pixels.

2. Application

Digital equipments which need color display, mobile navigator/video systems, tablet/notebook.


3. General Information

Item	Contents	Unit
Size	10.1	inch
Resolution	1024 (RGB) x 600	/
Interface	LVDS	/
Technology type	a-Si TFT	/
Pixel pitch	0.2175 x 0.2088	mm
Pixel Configuration	RGB stripes	
Outline Dimension (W x H x D)	235.0 x 143.0 x 6.5	mm
Active Area	222.72 x 125.28	mm
Display Mode	Normally white, Transmissive	/
Backlight Type	LED	/
Weight	TBD	g

4. Outline Drawing

PIN	FUNCTION	SYMBOL
1	VCOM	
2	VDD	
3	VDD	
4	NC	
5	REST	
6	STBYB	
7	GND	
8	Rxin0-	
9	Rxin0+	
10	GND	
11	Rxin1-	
12	Rxin1+	
13	GND	
14	Rxin2-	
15	Rxin2+	
16	GND	
17	RxCLK-	
18	RxCLK+	
19	GND	
20	Rxin3-	
21	Rxin3+	
22	GND	
23	NC	
24	NC	
25	GND	
26	NC	
27	DIM0/NC	
28	SELB	
29	AVDD	
30	GND	
31	LED K	
32	LED K	
33	L/R	
34	U/D	
35	VGL	
36	CARBEN/NC	
37	CARBEN/NC	
38	VGH	
39	LED A	
40	LED A	

TP:	PIN	OUT
1	X+	
2	Y-	
3	X-	
4	Y+	



LED CIRCUIT DIAGRAM:
13*3=39EA If=260mA

DETAIL A (4:1)
0.5±0.1, 2.0±0.1, 0.3±0.03, 3.5±0.3, 20.5±0.1, 19.5±0.05

DETAIL B
1.00±0.1, 0.50±0.05, P1X3=3.00±0.1, 5.00±0.1, 47.50±0.5

CONDUCTIVE STIFFENER PI
5.00±0.5, 5.00±0.5, 6.50±0.5, 5.0±0.3

BACK, FRONT

Dimensions:
 235.00±0.3 BL & TP
 223.52±0.3 TP V.A (4.74)
 223.12±0.3 TP A.A (4.94)
 222.72 LCD A.A (7.14)
 (116.51)
 8.85 (8.66)
 (8.46)
 125.28 LCD A.A
 125.68±0.3 TP A.A
 126.08±0.3 TP V.A
 143.00±0.3 BL & TP
 (71.49)
 10.1" TFT 1024*600*600
 12 o'clock
 104.90±0.5
 55.71±0.5

NOTES:

1. DISPLAY TYPE: 10.1" TFT, TRANSMISSIVE
2. VIEWING DIRECTION : U/L/D/R 65/65/55/65
3. Driver IC : Source HX8282-A14 Gate:HX8696-A
4. Top : -20° C ~ 70° C, Tst : -30° C ~ 80° C
5. GENERAL TOLERANCE: ±0.2
6. LCM Luminance:LED/400cd/m² (Typical)

DLC Display Co., Limited
www.dlcdisplay.com

DRAWN BY:	TITLE: DLC1010EZK-T-5	 SCALE: UNIT: mm SHEET NO: OF
CHECKED BY:	DWG NO:	
APPROVED BY:	DWG NAME:	
CONFIRMED BY:		

5. Interface signals

No	Symbol	Description	Remarks
1	VCOM	Common Voltage	
2	VDD	Power Voltage for digital circuit	
3	VDD	Power Voltage for digital circuit	
4	NC	No connection	
5	REST	Global reset pin	
6	STBYB	Standby mode, Normally pulled high STBYB="1", Normally operation STBYB="0", Timing controller, source driver will turn off, all output are High-Z	
7	GND	Ground	
8	RXIN0-	- LVDS differential data input	
9	RXIN0+	+LVDS differential data input	
10	GND	Ground	
11	RXIN1-	-LVDS differential data input	
12	RXIN1+	+LVDS differential data input	
13	GND	Ground	
14	RXIN2-	-LVDS differential data input	
15	RXIN2+	+LVDS differential data input	
16	GND	Ground	
17	RXCLK-	-LVDS differential clock input	
18	RXCLK+	+LVDS differential clock input	
19	GND	Ground	
20	RXIN3-	-LVDS differential data input	
21	RXIN3+	+LVDS differential data input	
22	GND	Ground	
23	NC	No connection	
24	NC	No connection	
25	GND	Ground	
26	NC	No connection	
27	NC	No connection	
28	SELB	6-bit / 8-bit mode select	Note 2
29	AVDD	Power for Analog Circuit	
30	GND	Ground	
31	LEDK	LED K	
32	LEDK	LED K	

33	L/R	Horizontal inversion	Note 4
34	U/D	Vertical inversion	Note 4
35	VGL	Gate off voltage	
36	CABCEN1/NC	CABC H/W enable/No connection	Note 3
37	CABCEN0/NC	CABC H/W enable/No connection	Note 3
38	VGH	Gate ON Voltage	
39	LEDA	LED A	
40	LEDA	LED A	

Note 1: The recommended FPC connector model is FH12S-40S-0.5SH manufactured by Hirose.

Note 2: If LVDS input data is 6 bits, SELB must be set to High;
If LVDS input data is 8 bits, SELB must be set to Low.

Note 3: When CABC_EN="00", CABC OFF.

When CABC_EN="01", user interface image.

When CABC_EN="10", still picture.

When CABC_EN="11", moving image.

When CABC off, don't connect DIMO, else connect it to backlight.

Note 4: When L/R="0", set right to left scan direction.


When L/R="1", set left to right scan direction.

When U/D="0", set top to bottom scan direction.

When U/D="1", set bottom to top scan direction.

Note 5: Definition of scanning direction

Refer to the figure as below:



6. Absolute maximum Ratings

6.1. Electrical Absolute max. ratings

Parameter	Symbol	MIN	MAX	Unit	Remark
Digital Supply Voltage	DVDD	-0.3	5.0	V	
TFT Gate on voltage	VGH	-0.3	40	V	
TFT Gate off voltage	VGL	-20	0.3	V	
Analog power supply voltage	AVDD	-0.5	15	V	

6.2. Environment Conditions

Item	Symbol	MIN	MAX	Unit	Remark
Operating Temperature	TOPR	-20	70	°C	
Storage Temperature	TSTG	-30	80	°C	

6.3. LED Backlight Absolute max. ratings

Item	Symbol	MIN	MAX	Unit	Remark
Forward current	ILED	-	25	mA	For each LED

7. Electrical Specifications

7.1 Electrical characteristics

GND=0V, Ta=25°C

Item	Symbol	MIN	TYP	MAX	Unit	Remark
Digital Supply Voltage	DVDD	3.0	3.3	3.6	V	
TFT Gate on voltage	VGH	20	21	22	V	
TFT Gate off voltage	VGL	-6.5	-5.5	-4.5	V	
Analog power supply voltage	AVDD	10.65	10.85	11.05	V	
TFT Common electrode voltage	VCOM	3.6	3.8	4.0	V	

7.2 LED Backlight

Ta=25°C

Item	Symbol	MIN	TYP	MAX	Unit	Remark
Forward Current	IF	-	260	-	mA	
Forward Voltage	VF	-	9.6	-	V	
LED lifetime	-	-	25,000	-	Hrs	

8. Command/AC Timing

8.1 Timing Conditions

8.1.1 AC Electrical Characteristics


TTL Mode AC Electrical Characteristics

Parameter	Symbol	MIN	TYP	MAX	Unit	Remark
VDD Power On Slew Rate	Tpor	-	-	20	Ms	From 0V to 90% VDD
GRB pulse width	Trst	50	-	-	Us	DCLK=65MHz
DCLK cycle time	Tcph	14	-	-	ns	
DCLK pulse duty	Tcwh	40	50	60	%	
VSD setup time	Tvst	5	-	-	ns	
VSD hold time	Tvhd	5	-	-	ns	
HSD setup time	Thst	5	-	-	ns	
HSD hold time	Thhd	5	-	-	ns	
Data set-up time	Tdsu	5	-	-	ns	D0[7:0],D1[7:0], D2[7:0] to DCLK
Data hold time	Tdhd	5	-	-	ns	D0[7:0],D1[7:0], D2[7:0] to DCLK
DE setup time	Tesu	5	-	-	ns	
DE hold time	Tehd	5	-	-	ns	
Output stable time	Tsst	-	-	6	us	10% to 90% target voltage. CL=90pF,R=10K ohm(cascade)
				3		


Data Input Format

TTL Mode Data Input mode

Vertical Timing



Horizontal Timing



Parallel RGB input Timing Table DE Mode

Parameter	Symbol	MIN	TYP	MAX	Unit
DCLK Frequency	Fclk	40.8	51.2	67.2	MHz
Horizontal Display Area	Thd	1024			DCLK
HSD Period	Th	1114	1344	1400	DCLK
HSD Blanking	Thb+thfp	90	320	376	DCLK
Vertical Display Area	Tvd	600			TH
VSD Period	Tv	610	635	800	TH
VSD Blanking	Tvbp + tvfp	10	35	200	TH


HV Mode Horizontal Timing

Parameter	Symbol	MIN	TYP	MAX	Unit
DCLK Frequency	Fclk	44.9	51.2	63	MHz
Horizontal Display Area	Thd	1024			DCLK
HSD Period	Th	1200	1344	1400	DCLK
HSD Pulse Width	Thpw	1	-	140	DCLK
HSD Back Porch	Thbp	160			DCLK
HSD Front Porch	Thfp	16	160	216	DCLK

Vertical Timing

Parameter	Symbol	MIN	TYP	MAX	Unit
Vertical Display Area	Tvd	600			TH
VSD Period	Tv	624	635	750	TH
VSD Pulse Width	Tvpw	1	-	20	TH
VSD Back Porch	Tvbp	23			TH
VSD Front Porch	Tvfp	1	12	127	TH

Timing Diagram Input Clock and Data Timing Diagram




8.2 Power Sequence


To prevent the device damage from latch up, the power on/off sequence shown below must be followed.

power on : VDD, GND -> AVDD, AGND -> V1 to V14

Power off : V1 to V14 -> AVDD, AGND -> VDD ,GND



Power on timing sequence



Power off timing sequence

Note: Low level = 3 FH, when NBW = L (Normally white)
 Low level = 00 H, when NBW = H (Normally black)

9. Optical Specification


Ta=25°C

Item	Symbol	Condition	Min	Typ.	Max.	Unit	Remark
Contrast Ratio	CR	$\theta=0^\circ$	320	400	-		Note1 Note2
Response Time	Tr	25°C	-	25	40	ms	Note1 Note3
	Tf			25	40		
View Angles	ΘT	$CR \geq 10$	-	65	-	Degree	Note 4
	ΘB		-	55	-		
	ΘL		-	65	-		
	ΘR		-	65	-		
Chromaticity	White	Brightness is on	x	0.28	0.31	0.35	Note5, Note1
			y	0.29	0.33	0.36	
Luminance	L		-	400	-	cd/m ²	Note1 Note6
Uniformity	U		70	75	-	%	Note1 Note7

Note 1: Definition of optical measurement system.

Temperature = 25°C(±3°C)

LED back-light: ON, Environment brightness < 150 lx




Note 2: Contrast ratio is defined as follow:

$$\text{Contrast Ratio} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$


Note 3: Response time is defined as follow:

Response time is the time required for the display to transition from black to white (Rise Time, T_r) and from white to black (Decay Time, T_f).




Note 4: Viewing angle range is defined as follow:

Viewing angle is measured at the center point of the LCD.



Note 5: Color chromaticity is defined as follow: (CIE1931)

Color coordinates measured at center point of LCD.



$$S = \frac{\text{area of RGB triangle}}{\text{area of NTSC triangle}} \times 100\%$$

Note 6: Luminance is defined as follow:

Luminance is defined as the brightness of all pixels “White” at the center of display area on optimum contrast.

Note 7: Luminance Uniformity is defined as follow:

Active area is divided into 9 measuring areas (Refer Fig. 2). Every measuring point is placed at the center of each measuring area.

$$\text{Uniformity (U)} = \frac{\text{Minimum Luminance(brightness) in 9 points}}{\text{Maximum Luminance(brightness) in 9 points}}$$




Fig. 2 Definition of uniformity

10. Environmental / Reliability Tests

No	Test Item	Condition	Judgment criteria
1	High Temp Operation	Ts=+70, 120hrs	Per table in below
2	Low Temp Operation	Ta=-20°C, 120hrs	Per table in below
3	High Temp Storage	Ta=+80°C, 120hrs	Per table in below
4	Low Temp Storage	Ta=-30°C, 120hrs	Per table in below
5	High Temp & High Humidity Storage	Ta=+40°C, 90% RH 120 hours	Per table in below (polarizer discoloration is excluded)
6	Thermal Shock (Non-operation)	-20°C 30 min~+70°C 30 min, Change time:5min, 10 Cycles	Per table in below
7	ESD (Operation)	C=150pF, R=330Ω, 5points/panel Air:±8KV, 5times; Contact:±4KV, 5 times;	Per table in below
8	Vibration (Non-operation)	Frequency range:10~55Hz, Stroke:1.5mm Sweep:10Hz~55Hz~10Hz 2 hours for each direction of X.Y.Z.	Per table in below
9	Shock (Non-operation)	60G 6ms, ±X,±Y,±Z 3times, for each direction	Per table in below
10	Package Drop Test	Height:80 cm, 1 corner, 3 edges, 6 surfaces	Per table in below

INSPECTION	CRITERION(after test)
Appearance	No Crack on the FPC, on the LCD Panel
Alignment of LCD Panel	No Bubbles in the LCD Panel No other Defects of Alignment in Active area
Electrical current	Within device specifications
Function / Display	No Broken Circuit, No Short Circuit or No Black line No Other Defects of Display

11. Precautions for Use of LCD Modules

11.1 Safety

The liquid crystal in the LCD is poisonous. Do not put it in your mouth. If the liquid crystal touches your skin or clothes, wash it off immediately using soap and water.

11.2 Handling

- A. The LCD and touch panel is made of plate glass. Do not subject the panel to mechanical shock or to excessive force on its surface.
- B. Do not handle the product by holding the flexible pattern portion in order to assure the reliability
- C. Transparency is an important factor for the touch panel. Please wear clear finger sacks, gloves and mask to protect the touch panel from finger print or stain and also hold the portion outside the view area when handling the touch panel.
- D. Provide a space so that the panel does not come into contact with other components.
- E. To protect the product from external force, put a covering lens (acrylic board or similar board) and keep an appropriate gap between them.
- F. Transparent electrodes may be disconnected if the panel is used under environmental conditions where dew condensation occurs.
- G. Property of semiconductor devices may be affected when they are exposed to light, possibly resulting in IC malfunctions.
- H. To prevent such IC malfunctions, your design and mounting layout shall be done in the way that the IC is not exposed to light in actual use.

11.3 Static Electricity

- A. Ground soldering iron tips, tools and testers when they are in operation.
- B. Ground your body when handling the products.
- C. Power on the LCD module before applying the voltage to the input terminals.
- D. Do not apply voltage which exceeds the absolute maximum rating.
- E. Store the products in an anti-electrostatic bag or container.

11.4 Storage

- A. Store the products in a dark place at $+25^{\circ}\text{C} \pm 10^{\circ}\text{C}$ with low humidity (40% RH to 60% RH). Don't expose to sunlight or fluorescent light.
- B. Storage in a clean environment, free from dust, active gas, and solvent.

11.5 Cleaning

- A. Do not wipe the touch panel with dry cloth, as it may cause scratch.
- B. Wipe off the stain on the product by using soft cloth moistened with ethanol. Do not allow ethanol to get in between the upper film and the bottom glass. It may cause peeling issue or defective operation. Do not use any organic solvent or detergent other than ethanol.

11.6 Cautions for installing and assembling

Bezel edge must be positioned in the area between the Active area and View area. The bezel may press the touch screen and cause activation if the edge touches the active area. A gap of approximately 0.5mm is needed between the bezel and the top electrode. It may cause unexpected activation if the gap is too narrow. There is a tolerance of 0.2 to 0.3mm for the outside dimensions of the touch panel and tail. A gap must be made to absorb the tolerance in the case and connector.

