



DSRT05A-F3



DSRT08A-F3

特点

- 隔离式插座、05A:16A, 08A:10A。
- 环保产品 RoHS REACH。

Features

- General socket,05A:16A,08A:10A.
- Green product RoHS REACH.

DSRT 08A-F 3-XXA (H)

产品大类:DSRT
Product Category:DSRT

脚位数量:05A,08A
Pin Number:05A,08A

保护方式:F:隔离式
Protect way:F:Separable structure

颜色:3:黑色
Colour:3:Black

环保:H
RoHS:H

性能参数 Performance parameters

技术参数 Technical parameters


产品型号 Product type	DSRT05A-F3	DSRT08A-F3
额定电流 Rated current	16A	10A
额定电压 Rated voltage	300V	
线圈/触点介质耐压 Coil/Contact dielectric voltage	4000V/S	
触点间介质耐压 Dielectric voltage between contact	2500V/S	
螺钉扭矩 Screw torque	1.0Nm	
外连接导线 External connection wire	20-14/0.5-2.5AWG/mm ²	
环境温度 Ambient temperature	-45~+85℃	
重量 Weight	22g	27g

配套继电器及附件 Supporting relays and accessories

产品型号 Product type	继电器 Relay	模块 Module	塑料扳扣 Plastic pull clasp	金属卡簧 Metal clamp spring
DSRT05A-F3	DRPT-1C	DMD	B-20A	—
DSRT08A-F3	DRPT-2C	DMD	B-20A	—

外形尺寸图、接线图 Overall dimensions, Wiring diagrams

DSRT05A-3



DSRT08A-3

