

# Basic Charger Specification (FCT345)



**LED indicator**

<b>Compatible cells</b>		AA / AAA (2, 4 cells), Pair charging
<b>Input Voltage</b>		AC 100-240V, 50-60Hz
<b>Charge Current</b>		AA: 330mA (2, 4cells) AAA: 160mA (2, 4cells)
<b>Charge Time</b>		
	AA (min.1900mAh)	Approx. 6 hrs
	AAA (min.750mAh)	Approx. 5 hrs
<b>Charge Control</b>		-ΔV, Timer
<b>LED Indicator</b>		Charging: Turn On; Fully charging: Turn Off; Abnormal: Flashing
<b>Safety function</b>		Timer, Over-discharge cell detection, Reverse polarity charging prevention, Primary cell & End-of-Life cell detection
<b>Temperature range</b>		0°C~35°C (Operating), -20°C~60°C (Storage)
<b>Safety approval</b>		PSE (Japan), BSMI (Taiwan), KC (South Korea)
<b>Dimensions / Weight</b>		108(L) x 68(W) x 28(H)mm / Approx. 100g
<b>Others</b>		A plug [Japan, USA, Taiwan, Thailand, China], SE plug [South Korea], C plug [Europe, SP, Russia], BF plug [UK, HK, SP], O plug [Australia]