




Cir- cuits	Dimension mm	
	L1	L2
2x2	2.00	4.00
2x3	4.00	6.00
2x4	6.00	8.00
2x5	8.00	10.00
2x6	10.00	12.00
2x7	12.00	14.00
2x8	14.00	16.00
2x9	16.00	18.00
2x10	18.00	20.00
2x11	20.00	22.00
2x12	22.00	24.00
2x13	24.00	26.00
2x14	26.00	28.00
2x15	28.00	30.00
2x16	30.00	32.00
2x17	32.00	34.00
2x18	34.00	36.00
2x19	36.00	38.00
2x20	38.00	40.00
2x21	40.00	42.00
2x22	42.00	44.00
2x23	44.00	46.00
2x24	46.00	48.00
2x25	48.00	50.00
2x26	50.00	52.00
2x27	52.00	54.00
2x28	54.00	56.00
2x29	56.00	58.00
2x30	58.00	60.00
2x31	60.00	62.00
2x32	62.00	64.00
2x33	64.00	66.00
2x34	66.00	68.00
2x35	68.00	70.00
2x36	70.00	72.00
2x37	72.00	74.00
2x38	74.00	76.00
2x39	76.00	78.00
2x40	78.00	80.00



RECOMMENDED P. C. B. LAYOUT

RoHS COMPLIANT

REV	ECN NO.	DESCRIPTION	DATE
A		RELEASE	AUG. 18'05
B		MODIFY HOUSING	APR. 18'07
C		MODIFY P/N	MAR. 23'11

SPECIFICATIONS

Current Rating:

1 Amp

Insulator resistance:

5000 Megohms Min.

Dielectric withstanding:

AC 500V/minute

Operating Temperature:

-40° ~ +105°C

Contact Material:

Phosphor Bronze

Insulator Material:

High Temperature Thermoplastic
+Glass Fibre UL94V-0

Color: Black

Finish:

Standard: Gold flash all over

TOLERANCE UNLESS
OTHERWISE SPECIFIED

LINEAR	ANGLE
X. ±	X° ±
.X ± 0.38	.X° ±
.XX ± 0.25	.XX° ±
.XXX ±	.XXX° ±

APPD	
CHKD	
DRAW	Z
	MAR. 23'2011

PROJECTION



UNITS

MM

SCALE

SIZE

A4



GOLD-TEK ELECTRIC CO., LTD.

TITLE

2.00mm Female Header

CPART NO.

PART NO.

FHDS**G22-4026-LF

CAD NO. 1642

F:\PDF\SOC\SOC-0354

SHEET

1 OF 1

圖面編號: GTKSD1575-C(1)