

sewoo

Advanced Desktop Label Printer

LK-B301IE



- Excellent Compatibility with industry standards
- Ultra Compact and Durable
- Easy to use and maintain
- Optional Auto cutter, Peeler, Wireless Interface (Wi-Fi, Bluetooth)
- Supports label design software "Label Cooker"
- Versatile Font Types & Barcodes Printing Supported



WiFi



Bluetooth



Barcode



Durable



Easy Loading



Fast Speed
152 mm/sec



Compact Design



Easy Replacement



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 6ips(152mm/sec)

Print Width

Up to 4.25”(108mm)

Resolution

203 dpi (8dots/mm)

Memory

1MB Main Flash, 16MB SDRAM,

8MB Font flash

Sensor

Gap, Black mark, Cover open

Power

Type : External SMPS

AC : 100~240Vac, 1.5A, 50/60Hz

DC : 24Vdc/2.5A



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

7.48” x 10.31” x 6.61”

(190 x 262 x 168 mm)

Weight (Kg)

3.35lb(1.52kg)



MEDIA CHARACTERISTICS

Media Type

Roll, Fanfold, Blackmark,

Continuous, Gap, punched hole,

Notch Sensor

Media Width

1”~4.5”(25.4~115mm)

Media Roll Diameter

Core : Ø 25.4(1”)

Roll Diameter Max : Ø127mm

Thickness

0.060~0.20mm



OPERATING CHARACTERISTICS

Operating Temperature

41 ~ 104°F(5 ~ 40°C)

Operating Humidity

25 ~ 85%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%



BARCODES

1D

Code39, Code128 with subsets

A/B/C/Auto, UCC/EAN-128,

Code93, Codabar, Interleaved 2

of 5, UPC-A, UPC-E, UPC-A and E

with 2 or 5 digit extension, EAN-8,

EAN-13, EAN-8 and 13 with 2 or 5

digit extensions, Postnet, Plessey,

MSI-3, German Post Code, Logmars,

Code11, UPC_Interleaved 2 of 5,

Industrial 2 of 5, Standard 2 of 5,

Planet, ANSI, Logmars

2D

MaxiCode, PDF 417, Data Matrix,

QR Code, MicroPDF417, AZTEC,

Code 49, CODABLOCK, RSS



SOFTWARE

Emulations

EPL II, ZPL II Command compatible

Drivers

Windows Driver

Linux Driver

Mac Driver

SDKs

Windows SDK

Android SDK

iOS SDK



INTERFACES

Standard

USB, Serial(RS-232C), Ethernet

Optional

Wi-Fi(802.11a/b/g/n),

Bluetooth Smart Ready (Bluetooth4.2+BLE)



CERTIFICATIONS

CE, FCC, KC, UL, CB



FONTS / GRAPHICS

EPL II

6 bitmapped

8x12, 10x16, 12x20, 14x24,

32x48, 24x24(KSC5601)

ZPL II

9 bitmapped

5×9, 7×11, 10×18, 10x18, 15×28,

13×26, 40×60, 13x21, 24x24

2 smooth scalable(English, Korean)



ACCESSORIES

Standard

Power Cord, Power Supply,

Interface Cable(USB,Serial)

Optional

Auto cutter, Peeler

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprnter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

