

L Series

Bill Acceptor

- Multinational currencies acceptable
- New generation design of verification system
- Anti-string technology
- Selective interfaces
- Multicolor illumination bezel design
- Coin resistant bezel. (L77F)



ict

L Series

Bill Acceptor

The L Series bill acceptor combines improved bill-sensing technology with lightweight and durable plastic construction. It also features fast software updating, and easy maintenance to increase acceptance rates and reduce bill jammed.



PL77



L70

L70P5



L83

L83P6



L77

L77P6



L83

L83P3



L77F

L77FP6

L Series

Specifications



Acceptance Rate

96% or greater



Bill Insertion

Four-way



Bill Width Accepted

L70-P2/P5, L70#-P2/P5, L70(IGT)-P2/P5:
59~67mm/ 2.32~2.64 inches(67mm)
59~71mm / 2.32~2.8 inches(71mm)
L77F-P2/P5:
72~77mm/ 2.83~3.03 inches
L77-P3/P6, L77#-P3/P6:
61~77mm/ 2.40~3.03 inches
L83-P3/P6, L83#-P3/P6:
61~83mm/ 2.40~3.27 inches
PL77-P3/P6:
61~77mm/ 2.40~3.03 inches



Acceptance Speed

Approx. 3 seconds to cash box



Capacity

L70-P2, L70#-P2, L70(IGT)-P2: Approx. 200 notes
L70-P5, L70#-P5, L70(IGT)-P5: Approx. 500 notes
L77-P3, L77#-P3: Approx. 300 notes
L77-P6, L77#-P6: Approx. 600 notes
L83-P3, L83#-P3, PL77-P3: Approx. 300 notes
L83-P6, L83#-P6, PL77-P6: Approx. 600 notes
L77F-P2: Approx. 150 notes
L77F-P5: Approx. 500 notes



Interface

L70-P2/P5, L70#-P2/P5:
Pulse, RS232, ID003 &
CCNET compatible, MDB
L70(IGT)-P2/P5:
Pulse, RS232, IGT (ID022 compatible),
ID003 Compatible
L77-P3/P6:
Pulse, GBA & CCNET &
ID003 compatible, RS232,
ccTalk, MDB, Parallel
L77F-P2/P5:
ccTalk, CCNET & ID003 compatible,
Pulse, RS232, MDB
L83-P3/P6:
Pulse, GBA & CCNET & ID003 compatible,
RS232, ccTalk, MDB, Parallel
PL77-P3/P6:
Pulse, GBA & CCNET & ID003 compatible,
RS232, ccTalk, MDB, Parallel
L83#-P3/P6:
Pulse, GBA & CCNET & ID003 compatible,
RS232, MDB
L77#-P3/P6:
Pulse, GBA & CCNET & ID003 compatible,
RS232, MDB



Power Source

L70# / L77# / L77F / L83#: 12V DC(10~16V DC)
Others: 12V DC(10.8~13.2V DC)



Power Consumption

Standby: 0.3A, 3.6W
Operation: 1.2A, 14.4W
Maximum: 2A, 24W



Dimension

L70, L70#, L70(IGT):
102.8 x 134.0 x 132.1 mm/ 4.05 x 5.28 x 5.20 inches
L70-P2, L70#-P2, L70(IGT)-P2:
102.8 x 285.7 x 188 mm/ 4.05 x 11.25 x 7.40 inches
L70-P5, L70#-P5, L70(IGT)-P5:
102.8 x 285.7 x 216.8 mm/ 4.05 x 11.25 x 8.54 inches
L77, L77#:
17.4 x 132 x 147.5 mm/ 4.62 x 5.2 x 5.81 inches
L77P3, L77#-P3:
121.7 x 265.5 x 222.2 mm/ 4.79 x 10.45 x 8.75 inches
L77P6, L77#-P6:
121.7 x 265.5 x 269.2 mm/ 4.79 x 10.45 x 10.6 inches
L77F:
102.4 x 134 x 88.8 mm/ 4.03 x 5.28 x 3.5 inches
L77F-P2:
102.4 x 272.6 x 130.6 mm/ 4.03 x 10.73 x 5.14 inches
L77F-P5:
102.4 x 272.6 x 179 mm/ 4.03 x 10.73 x 7.05 inches
L83, L83#:
117.4 x 86.1 x 138.5 mm/ 4.62 x 3.39 x 5.45 inches
L83P3, L83#-P3:
121.7 x 265.5 x 222.2 mm/ 4.79 x 10.45 x 8.75 inches
L83P6, L83#-P6:
121.7 x 265.5 x 269.2 mm/ 4.79 x 10.45 x 10.6 inches
PL77:
113.4 x 132 x 143.9 mm/ 4.46 x 5.2 x 5.67 inches
PL77P3:
121.7 x 276 x 218.5 mm/ 4.79 x 10.87 x 8.6 inches
PL77P6:
121.7 x 276 x 266 mm/ 4.79 x 10.87 x 10.47 inches



Weight

L70, L70#, L70(IGT):
Approx. 0.52kg/ 1.15 lbs
L70-P2, L70#-P2, L70(IGT)-P2:
Approx. 1.25kg/ 2.76 lbs
L70-P5, L70#-P5, L70(IGT)-P5:
Approx. 1.4 kg/ 3.09 lbs
L77, L77#:
Approx. 0.8 kg/ 1.76 lbs
L77F:
Approx. 0.44kg/ 0.97 lbs
L77F-P2:
Approx. 1.35kg/ 2.98 lbs
L77F-P5:
Approx. 1.42kg/ 3.13 lbs
L77-P3, L77#-P3:
Approx. 1.46kg/ 3.22 lbs
L77-P6, L77#-P6:
Approx. 1.65kg/ 3.64 lbs
L83, L83#, PL77:
Approx. 0.8 kg/ 1.76 lbs
L83-P3, L83#-P3, PL77-P3:
Approx. 1.46kg/ 3.22 lbs
L83-P6, L83#-P6, PL77-P6:
Approx. 1.65kg/ 3.64 lbs




Environmental

Operation Temperature:
L70/ L77/ L83/ PL77: 0°C/ 32°F~55°C/ 131°F
L77F: 0°C/ 32°F~60°C/ 140°F
L70#/ L77#/ L83# : 0°C/ 32°F ~65°C/ 149°F
Storage Temperature: -20°C/ -4°F~70°C/ 158°F
Humidity: 30%~85% RH (no condensation)



Recommended Applications

Amusement, Gaming, Vending



ict

Specifications are subject to change without prior notice.



International Currency Technologies

Chi Hong Building, No.24, Alley 38, Lane 91, Nei Hu Road, Sec. 1, Taipei, Taiwan

Phone : +886-2-2797-1238

Fax : +886-2-2797-1634

Email : sales@ictgroup.com.tw (Product Information)

rma@ictgroup.com.tw (Technical Service)

Website : www.ictgroup.com.tw
