


NOTES:

- 7.0INCH PROJECTIVE CAPACITIVE TOUCH PANEL.
- OPERATING VOLTAGE: VDD=3.3V.
- COVER GLASS + SENSOR GLASS + FPCA.
- RESOLUTION: 800 X 480 DOTS.
- IC DRIVER: FT5426 (SMT).
- MULTI FINGER: UP TO 5.
- HARDNESS OF COVER SURFACE: 7H.
- TRANSTTANCE: $\geq 85\%$.
- ELECTRODES: 27 X 16.
- UV GLUE AROUND CHIP PINS.
- GROUNDING LAYERS ON BOTH SIDES OF FPC.
- ITO PATTERN ON BOTH SIDES CAN NOT BE VISIBLE UNDER FRONT BRIGHTNESS.
- 0.5MM THICKNESS OF TINY COMPRESIBLE GASKET.
- PROTECTIVE CIRCUITS AT INPUT SIGNALS LINES.
- PROTECTIVE FILMS ON FRONT AND BACK SIDES OF MODULE.
- OPERATION TEMP.: -20°C TO 70°C ;
STORAGE TEMP.: -30°C TO 80°C .
- GENERAL TOLERANCE: ± 0.2 .
- RoHS COMPLIANT.



DETAIL A
SCALE: 4/1

FPC ASSIGNMENT:

1	VSS
2	VDD
3	SCL(SSEL)
4	NC(SCK)
5	SDA(MOSI)
6	NC(MISO)
7	RST
8	NC
9	INT
10	VSS



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	VICTOR	2015.08.25	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	MI0700CUP-C4
APPROVED BY:				DESCRIPTION:
VERSION NO:	01			CTP MODULE

01	FIRST ISSUE	2015.08.25
	DATE	VERSION NO: