

# MR850, MR851, MR852, MR854, MR856

MR852 and MR856 are Preferred Devices

## Axial Lead Fast Recovery Rectifiers

Axial lead mounted fast recovery power rectifiers are designed for special applications such as dc power supplies, inverters, converters, ultrasonic systems, choppers, low RF interference and free wheeling diodes. A complete line of fast recovery rectifiers having typical recovery time of 100 nanoseconds providing high efficiency at frequencies to 250 kHz.

### Features

- These are Pb-Free Devices\*

### Mechanical Characteristics:

- Case: Epoxy, Molded
- Weight: 1.1 Gram (Approximately)
- Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable
- Lead and Mounting Surface Temperature for Soldering Purposes: 220°C Max. for 10 Seconds, 1/16" from Case
- Available Tape and Reeled, 1200 per Reel, by adding a "RL" Suffix to the Part Number
- Polarity: Cathode Indicated by Polarity Band



**ON Semiconductor®**


<http://onsemi.com>

## FAST RECOVERY POWER RECTIFIERS 3.0 AMPERES, 50–600 VOLTS



AXIAL LEAD  
CASE 267-05  
STYLE 1

### MARKING DIAGRAM



A = Assembly Location  
MR85x = Device Number  
          x = 0, 1, 2, 4 or 6  
YY = Year  
WW = Work Week  
■ = Pb-Free Package

(Note: Microdot may be in either location)

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 3 of this data sheet.

**Preferred** devices are recommended choices for future use and best overall value.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MR850, MR851, MR852, MR854, MR856

## MAXIMUM RATINGS

Rating	Symbol	MR850	MR851	MR852	MR854	MR856	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	$V_{RRM}$ $V_{RWM}$ $V_R$	50	100	200	400	600	V
Non-Repetitive Peak Reverse Voltage	$V_{RSM}$	75	150	250	450	650	V
RMS Reverse Voltage	$V_{R(RMS)}$	35	70	140	280	420	V
Average Rectified Forward Current (Single phase resistive load, $T_A = 80^\circ\text{C}$ )	$I_O$	3.0					A
Non-Repetitive Peak Surge Current (Surge Applied at Rated Load Conditions)	$I_{FSM}$	100 (one cycle)					A
Operating and Storage Junction Temperature Range	$T_J, T_{stg}$	- 65 to +125 - 65 to +150					$^\circ\text{C}$

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

## THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction-to-Ambient (Recommended Printed Circuit Board Mounting)	$R_{\theta JA}$	28	$^\circ\text{C/W}$

## ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Min	Typ	Max	Unit
Forward Voltage ( $I_F = 3.0\text{ A}$ , $T_J = 25^\circ\text{C}$ )	$V_F$	–	1.04	1.25	V
Reverse Current (rated DC voltage) $T_J = 25^\circ\text{C}$ <div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"><math>T_J = 80^\circ\text{C}</math></div> <div style="font-size: 2em;">{</div> <div style="margin-left: 5px;"> MR850 MR851 MR852 MR854 MR856 </div> </div>	$I_R$	– – – – –	2.0 – 60 – – 100	10 150 150 200 250 300	$\mu\text{A}$

## REVERSE RECOVERY CHARACTERISTICS

Characteristic	Symbol	Min	Typ	Max	Unit
Reverse Recovery Time ( $I_F = 1.0\text{ A}$ to $V_R = 30\text{ Vdc}$ ) ( $I_F = 15\text{ A}$ , $di/dt = 10\text{ A}/\mu\text{s}$ )	$t_{rr}$	– –	100 150	200 300	ns
Reverse Recovery Current ( $I_F = 1.0\text{ A}$ to $V_R = 30\text{ Vdc}$ )	$I_{RM(REC)}$	–	–	2.0	A

## MR850, MR851, MR852, MR854, MR856

### ORDERING INFORMATION

Device	Package	Shipping†
MR850	Axial Lead*	500 Units / Box
MR851	Axial Lead*	500 Units / Box
MR851RL	Axial Lead*	1200 / Tape & Reel
MR851RLG	Axial Lead*	1200 / Tape & Reel
MR852	Axial Lead*	500 Units / Box
MR852G	Axial Lead*	500 Units / Box
MR852RL	Axial Lead*	1200 / Tape & Reel
MR852RLG	Axial Lead*	1200 / Tape & Reel
MR854	Axial Lead*	500 Units / Box
MR854G	Axial Lead*	500 Units / Box
MR854RL	Axial Lead*	1200 / Tape & Reel
MR854RLG	Axial Lead*	1200 / Tape & Reel
MR856	Axial Lead*	500 Units / Box
MR856G	Axial Lead*	500 Units / Box
MR856FF	Axial Lead*	500 Units / Fan-Fold
MR856FFG	Axial Lead*	500 Units / Fan-Fold
MR856RL	Axial Lead*	1200 / Tape & Reel
MR856RLG	Axial Lead*	1200 / Tape & Reel


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*These packages are inherently Pb-Free.

# MR850, MR851, MR852, MR854, MR856

## PACKAGE DIMENSIONS

### AXIAL LEAD CASE 267-05 ISSUE G




#### NOTES:

1. DIMENSIONS AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 267-04 OBSOLETE, NEW STANDARD 267-05.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.287	0.374	7.30	9.50
B	0.189	0.209	4.80	5.30
D	0.047	0.051	1.20	1.30
K	1.000	---	25.40	---

#### STYLE 1:

- PIN 1. CATHODE (POLARITY BAND)  
2. ANODE

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA  
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your  
local Sales Representative.