

San Guang Electronics Co., Ltd.

No. 35, Sec. 1, Chung Hwa Rd., Hsin Chu, Taiwan, R.O.C.

TEL: 886-3-5322105~6 FAX: 886-3-5325952

NE-2H 6x22x30 B

Characteristics	Item	Specification	Item	Specification						
	Applied Voltage	110 VAC	Current Output	Approx. 1.5 mA						
	Series Resistor	33K Ω	Corona	40% MIN						
	Breakdown Voltage	95 VAC Max	Life (hours)	25,000 Min						
Dimension										
	单位: mm									
Material	(1)	Glass Tube	1	Lead Glass		(4)	Lead Wire	2	DU Wire	$\phi 0.4 \times 35$
	(2)	Gas			Ne+Ar(0.02%)					
	(3)	Lead Wire	2	NI Wire	$\phi 0.9 \times 8$					
Aspect	(1) The concave, broken, crack and black splattering of glass tube is not allowed									
	(2) The critical defected shape of Neon Lamp tip is not acceptable.									
	(3) Lead wire is tin-plated.									

P.S. Uses 33 Kohm series resistor, and lights the Neon Lamp with applied voltage, the time of breakdown voltage up to "90% of the applied voltage" is the Lamp's lifetime.