

San Guang Electronics Co., Ltd.

No. 35, Sec. 1, Chung Hwa Rd., Hsin Chu, Taiwan, R.O.C.

TEL: 886-3-5322105~6 FAX: 886-3-5325952

NE-2 6x16x50

Characteristics	Item	Specification	Item	Specification
	Applied Voltage	110 VAC	Current Output	Approx. 0.7 mA
	Series Resistor	68 K Ω	Corona	80% MIN
	Breakdown Voltage	65 VAC Max	Life (hours)	25000 MIN

Dimension										
	<p>单位: mm</p>									
Material	(1)	Glass Tube	1	Glass	(RoHS)	(4)	Lead Wire	2	DU Wire	$\phi 0.4 \times 54$
	(2)	Gas			Ne+Ar(0.5%)					
	(3)	Lead Wire	2	NI Wire	$\phi 0.9 \times 6$					
Aspect	(1)The concave, broken, crack and black splattering of glass tube is not allowed									
	(2) The critical defected shape of Neon Lamp tip is not acceptable.									
	(3) Lead wire is tin-plated.									

P.S. Uses 68 Kohm series resistor, and lights the Neon Lamp with applied voltage, the time of breakdown voltage up to “90% of the applied voltage” is the Lamp’s lifetime.