

Thermocouples

for use with Reflow Tracker® systems

PA0210 FAST RESPONSE EXPOSED JUNCTION

This is the standard thermocouple used throughout the reflow industry and is constructed from type K thermocouple wire. Each conductor is PTFE insulated and then twisted together to prevent tangling in use. The wire diameter is 0.2 mm (.007 in), providing a good compromise between size and strength. The thermocouple tip is pre-tinned to ease soldering to the PCB. We recommend the use of an activated flux and high temperature solder to attach this thermocouple to the PCB assembly.

Thermocouple Material	Type K Special Limits of Accuracy
Accuracy	±1.1°C or 0.4% of the reading (whichever is greater)
Length	800 mm (31.4 in)*
Conductor Diameter	0.2 mm (.007 in)
Temperature	265°C (509°F) maximum

* Other lengths available on request

PA1683 FINE WIRE

This thermocouple has been developed specifically for use with BGA and ultra fine pitch surface mount components. The type K thermocouple conductors are 0.1 mm (.003 in) in diameter, each insulated with PTFE. The two conductors are then over-wrapped with a single outer PTFE sheath to prevent tangling in use. The recommended attachment method is activated flux and high temperature solder. For BGA, the accepted practice is to drill through the PCB and insert the tip until it touches a ball, and then bond the thermocouple wire in place.

Thermocouple Material	Type K to British Standard Class I
Accuracy	±1.5°C or 0.4% of the reading (whichever is greater)
Length	500 mm (19.6 in)
Conductor Diameter	0.1 mm (.003 in)
Temperature	265°C (509°F) maximum

PA1571 ULTRA FINE DIAMETER, MINERAL INSULATED

The PA1571 is intended for use in high temperature applications. It is a Type K mineral insulated thermocouple with an Inconel outer sheath. The overall diameter is 0.5 mm (.01 in). It can operate to 1000°C (1832°F). Attachment method will depend on the application, but can include ceramic cement or mechanical fixtures.

Thermocouple Material	Type K to British Standard Class I
Accuracy	±1.5°C or 0.4% of the reading (whichever is greater)
Length	600 mm (23.6 in)
Conductor Diameter	NA (outer sheath is 0.5 mm / .01 in)
Temperature	1000°C (1832°F) maximum

PA0215 FIBER INSULATED PROBE

Exposed junction type K thermocouple constructed from 0.2 mm (.007 in) wire with glass fiber insulation. This probe is designed for continuous use up to 500°C (932°F) and is, therefore ideally suited to high temperature soldering applications. For best results, we recommend that the probe is attached using an activated flux and high temperature solder.

Thermocouple Material	Type K Special Limits of Accuracy
Accuracy	±1.1°C or 0.4% of the reading (whichever is greater)
Length	800 mm (31.4 in)
Conductor Diameter	0.2 mm (.007 in)
Temperature	500°C (932°F) maximum

The Worldwide Leader in Temperature Profiling



Europe and Asia
 DATAPAC Limited,
 Deanland House, 160 Cowley Road,
 Cambridge CB4 0GU, UK
 Tel: +44 (0)1223 423 141
 Fax: +44 (0)1223 423 306
 E-mail: sales@datapac.co.uk
 Web: www.datapac.com

North and South America
 DATAPAC Inc.,
 187 Ballardvale Street,
 Willmington, MA 01887, USA
 Tel: +1 978 988 9000
 Fax: +1 978 988 0666
 E-mail: sales@datapac.com
 Web: www.datapac.com

Germany
 DATAPAC GmbH,
 Valdorfer Straße 100
 D-32602 Vlotho, Deutschland
 Tel: +49 5733 9107 0
 Fax: +49 5733 9107 27
 E-mail: sales@datapac.de
 Web: www.datapac.de



www.datapac.com

© 2011 Datapac
 (Q18 Thermocouples Rev B) 6/2011
 Datapac, the Datapac logo and Reflow Tracker
 are registered trademarks of Datapac.
 Specifications subject to change without notice.