

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除专利等明确授权外, 否则禁止转让、复制、引用、交流本文件的内容, 否则将承担侵权责任。侵犯专利等明确授权的, 侵权者将承担侵权责任。 本公司保留对涉及发明、实用新型和外观设计的所有权利。

FOR-1755 Rev.1.8

2





3

4

5

6

未注公差/General tolerances(mm)													 0.1/10  ±2°
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50



5	Cage	Copper alloy	M3/Ni Plated
4	Screw	Copper alloy	M3/Ni Plated
3	Current Carrier	Copper	Sn Plated
2	Screw	Copper alloy	Ni Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)		300/30	/	300/10
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	/	/
额定电压/电流/Rated Voltage(V)/Current(A)		500/32	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		6	/	/
螺丝扭矩/Torque Tightening(N·m/Lb.in)		M3, 0.5/4.43		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)		10~30/ 0.2~4		
间距/Pitch(mm)/线数范围/Poles		6.2/N=01P		
剥线长度/Stripping length(mm)		8~10		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		
标准颜色编号/Standard color number: PANTONE / RAL		/		

		MATERIAL: /		SURFACE/COLOR: /		
		MAT NO./REV: /		MAT STATUS: 批量		
APPD: Peng M	2023. 09. 11	NAME PC4-TW-01P-11-00Z (H)				
CHKD: Gao WG	2023. 09. 11					
DRFT: Ye XD	2023. 09. 11	DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
 A4		/	CUSTOMER DRAWING	work	1:1	1/1

00	/	New Product	Ye XD	2023. 09. 11
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6