





Cir- cuits	Dimension mm	
	L1	L2
2X2	2.54	5.08
2X3	5.08	7.62
2X4	7.62	10.16
2X5	10.16	12.70
2X6	12.70	15.24
2X7	15.24	17.78
2X8	17.78	20.32
2X9	20.32	22.86
2X10	22.86	25.40
2X11	25.40	27.94
2X12	27.94	30.48
2X13	30.48	33.02
2X14	33.02	35.56
2X15	35.56	38.10
2X16	38.10	40.64
2X17	40.64	43.18
2X18	43.18	45.72
2X19	45.72	48.26
2X20	48.26	50.80
2X21	50.80	53.34
2X22	53.34	55.88
2X23	55.88	58.42
2X24	58.42	60.96
2X25	60.96	63.50
2X26	63.50	66.04
2X27	66.04	68.58
2X28	68.58	71.12
2X29	71.12	73.66
2X30	73.66	76.20
2X31	76.20	78.74
2X32	78.74	81.28
2X33	81.28	83.82
2X34	83.82	86.36
2X35	86.36	88.90
2X36	88.90	91.44
2X37	91.44	93.98
2X38	93.98	96.52
2X39	96.52	99.06
2X40	99.06	101.60

RoHS COMPLIANT



RECOMMENDED P. C. B. LAYOUT

REV	ECN NO.	DESCRIPTION	DATE
A		RELEASE	JUN. 02'09
B		MODIFY P/N	MAR. 31'11

SPECIFICATIONS

Current Rating:

3 Amp

Voltage Rating:

230V

Insulator resistance:

5000 Megohms Min.

Contact Resistance:

20 m ohms Max.

Dielectric withstanding:

AC 1000V/minute

Operating Temperature:

-40° ~ +105°C

Contact Material:

Brass

Insulator Material:

Polyester UL94V-0

Standard Color: Black

Finish:

Gold plated

TOLERANCE UNLESS
OTHERWISE SPECIFIED

LINEAR	ANGLE
X. ± 0.50	X° ±
.X ± 0.38	.X° ±
.XX ± 0.25	.XX° ±
.XXX ±	.XXX° ±

APPD

CHKD

DRAW

Z

MAR. 31'2011

PROJECTION



UNITS

MM

SCALE

SIZE

A4



GOLD-TEK ELECTRIC CO., LTD.

TITLE
2.54mm Pin Header
Dual Row Straight
Type

CPART NO.

PART NO.
PHDS**G11-B034

CAD NO. I642

F:\PDF\PH\PH-0433

SHEET

1 OF 1

圖面編號:GTKGS1892-B(1)