





REVISION:A

REV

DESCRIPTION

APPR

DATE

**RoHS compliance**

Mechanical:(mm)

A:Max 7.00

B:Max 10.5

C:2.5 ± 1.00

Net Weight:0.53g/Pcs

Materials:

1. Core:FE-0944-386

2. Pins:PW-0246/47-114

3. Wire:CW-1084-184

4. Sleeve Tube:PE-0273-270

5. Coating Epoxy:CO-0096/97-381

Reports:

SGS NO:RLSZB000278000001

SGS NO:CANEC0905266801

SGS NO:RLSZB000326890001

UL NO:E204861

SGS NO:CANEC0900768501

UL NO:E203950

SGS NO:CANEC0901191402

UL NO:E73015

CO-0001/02-14 SGS NO:RLSZB000140520001

6. SOLDER:SB-0007-155

SGS NO:EC409356502

7. FLUX:CO-0088-232

SGS NO:EC409602700

8. Carton

SGS NO:GZ0902007998/CHEM

Electrical Characteristic:

1. Tested Condition:1KHz/0.25V

2. Inductance:3.3uH±10%


3. DCR:Max 0.04Ω

4. IDC:0.3A

Temp:-20℃ ~ +80℃

Others:NO

Schematic:



東莞高瞻電子元件制品有限公司

參考文件

東莞高瞻電子元件制品有限公司

受控文件副本

Tested Instrument:

☐ Transformer Auto Tester CH-3200A☐ Withstand Voltage Tester 9605☒ Current Meter CH-301A☒ LCZ Meter CH-1061☐ Q Meter HM2801A☐ L-SRF HM2770A

Approval By Customer

Control Document Specify

DONGGUAN TOP-VIEW ELECTRONICS
COMPONENTS LTD.

Tel:0769-83913778 Fax:0769-83915551

TOP-VIEW P/N: PK-DR2W5x7-3R3K-A04X-BK-OT

TOP-VIEW ISSUE NO: TV-CE-SS-15872

TOP-VIEW Test Report No:

SZHH00368135

CUSTOMER P/N:

LINEAR UNIT mm

GENERAL TOLERANCE

GENERAL RAD/FILLET R0.20

ANGULAR UNIT DEGREE

GENERAL TOLERANCE ±1/2°

GENERAL DRAFT 1° MAX

DESIGN

DRAW

CHECK

APPROVED

/ /

07/11/08

07/11/08

07/11/08

SHEET 1 OF 1

SHEET SIZE A4