



REVISION: A



REV

DESCRIPTION

APPR

DATE

RoHS

RoHS compliance

Mechanical:(mm)

A:Max 11.0

B:Max 13.0

C:5.0 ± 1.00

Net Weight:2.57g/Pcs

Materials:

1. Core:FE-0272-33

2. Pins:PW-0238/239-114

3. Wire:CW-1079-184

4. Sleeve Tube:PE-0276-270

5. SOLDER:SB-0007-155

6. FLUX:CO-0088-232

7. Carton

Reports:

SGS NO:CE/2011/53953

SGS NO:CANEC1005393003

SGS NO:RLSZC000676230001

UL NO:E204861

SGS NO:CANEC0900768501


UL NO:E203950

SGS NO:EC409356502

SGS NO:EC409602700

SGS NO:GZ0902007998/CHEM

Schematic:



東莞高瞻電子元件制品有限公司

參考文件

東莞高瞻電子元件制品有限公司

受控文件副本

Tested Instrument:

☐ Transformer Auto Tester CH-3200A☐ Withstand Voltage Tester 9605☒ Current Meter CH-301A☒ LCZ Meter CH-1061☐ Q Meter HM2801A☐ L-SRF HM2770A

Electrical Characteristic:

1. Tested Condition:1KHz/0.25V

2. Inductance:2.2mH±20%

3. DCR:Max 3.9Ω

Temp:-20℃ ~ +80℃

Others:NO

Approval By Customer

Control Document Specify

DONGGUAN TOP-VIEW ELECTRONICS
COMPONENTS LTD

Tel:0769-83913778 Fax:0769-83915551

TOP-VIEW P/N: PK-DR2W8x10-222M-3R9X-BK-N

TOP-VIEW ISSUE NO: TV-CE-SS-15187

TOP-VIEW Test Report No:
RLSZD00099406

CUSTOMER P/N:

LINEAR UNIT mm

GENERAL TOLERANCE

GENERAL RAD/FILLET R0.20

ANGULAR UNIT DEGREE

GENERAL TOLERANCE ±1/2°

GENERAL DRAFT 1° MAX

DESIGN

DRAW

CHECK

APPROVED

/ /

K.Z.H

Zh.S.H

A.M.R.

/ /

07/06/18

07/06/18

07/06/18

SHEET 1 OF 1 SHEET SIZE A4