



MC-306
XTAL (kHz)

Product No. / Ordering code :Q13MC30610002

Brief sheet		Data sheet		ROHS	REACH
 English	 Japanese	 Chinese	—	 English	 English

Specification

Mounting Type	Surface Mount	Model name item name use	MC-306
Size (LxWxH)	8 x 3.8 x 2.54 mm	Motional resistance (Max)	50kΩ
Customer load capacitance	9pF	Level of Drive(Max)	1μW
Frequency tolerance	+/-20.0ppm	Turnover temperature	+25°C +/-5°C
Operating Temperature	-40 to +85°C	Parabolic coefficient (Max)	-0.04 x 10 ⁻⁶ /°C ²
Extra Options	N/A	Frequency aging	+/- 3 ppm
Frequency	32.768000kHz	Terminal plating(Sales)	Sn-Bi

[Back](#)

PRODUCTS

- ▶ Crystal Oscillator
- ▶ Real Time Clock
- ▶ Crystal Unit
- ▶ Automotive Solutions
- ▶ Sensor
- ▶ Timing Module

APPLICATIONS

- ▶ Common Block Diagram
- ▶ Individual Block Diagram

IC Partners

- ▶ Circuit design information
- ▶ IC Partners information

INFORMATION

- ▶ RTC Module Technical Tools
- ▶ Programmable XO Information
- ▶ Video Contents
- ▶ Support
- ▶ Technical Information
- ▶ Precaution
- ▶ Discontinued products
- ▶ Higher Quality / Green Purchasing / Business continuity management
- ▶ Sales Office and Plants

NEWS

- ▶ What's new
- ▶ News Release
- ▶ New products

CONTACT

- ▶ Contact
- ▶ Online distributor