


## Full Page Passport Reader

Full Page Passport Reader is a compact, fast and multi-functional document reader based on OCR technology. It is designed for extracting data from ICAO standard travel documents. It provides ideal solutions for identifying Passports, Visa, ID cards, Driver License and other travel documents.





Read ICAO compliant & Non-ICAO documents



Combine with high accuracy OCR SDK



Obtain digital data from contactless chips(RFID)



Applicable for self-service kiosk



Capture images in white, IR & UV Illuminations



Provide OCR customization service

## Applications



Airport Border Control

## Specification



Security Access Control



Hotel Property Management





Finance Payment Process


Supported Documents
---------------------

		ICAO 9303 standard compliant documents:	
	Machine Readable Zone	ID-1 (Identity Card)	
		ID-2 (Visa)	
		ID-3 (Passport)	
	Visual Inspection Zone	Customization based on clients' requirements	
	Barcode	1D: Code 128, Code 39, Interleaved 2 of 5 2D: PDF 417, QR Code, Data Matrix , Aztec Code	

Image				
Resolution	500 DPI			
Illumination	Visible, IR			
Color Depth	24 bits/pixels			
Sensor	CMOS, 5.0 Megapixels (2592*1944)			
Image Format	JPG, BMP, PNG			
Field of View	127mm*88mm			
	Software			
Supported Operation System	Windows 7,8,10,Vista,XP (32/64 bit WHQL certified) Windows Server 2003 & 2008 (32/64 bit) Linux Ubuntu, CentOS, RedHat Android			
Development kit	Complete OCR SDK including DLLs, OCXs, WebSocket, Samples and Demo program			
Programming Languages	C#, C/C++, Java, Delphi, Visual Basic 6.0, VB.NET			
Security Check	UV Dull Paper Check; MRZ Comparison; Portrait Comparison; IR B900 Ink check.			







Hardware				
Dimension	175*199*140mm(width*depth*height)			
Weight	1.75kg (Net)			
weight	2.00kg (Gross)			
Interface	USB 2.0			
Status LEDs	Power, Ready, Error and Warning			
Buzzer	Build-in buzzer			
Power	Input: AC 100~240V, 50-60Hz, 0.8A			
i owei	Output: DC 12V, 2A			
Operating humidity	20%-95%(non-condensing)			
Operating tomperature	-10°C to 50°C operating			
Operating temperature	-20°C to 50°C storage			
Warranty	1 year warranty, extensible			

## Sinosecu Technology Corporation

(\$\mathbf{V}\$+86(0)1082525969
(\$\mathbf{B}\$) +86 10 6280 0256
(\$\mathbf{B}\$) www.sinosecu.com.cn/en/
(\$\mathbf{O}\$) 6th Floor, CETC TaiJi Information Industrial Park Tower B, No.7 Rongda Rd. Chaoyang Beijing, China