

# Robot Accessories

## Servo Motor (GWS)

### PICO/STD/JR

#### SPECIFICATION

Size(mm) : 22.8(L) x 9.5(W) x 16.5(H)

Weight(g) : 5.40

Speed(sec/60) : 0.12/4.8V 0.09/6V

Torque(kg-cm) : 0.7/4.8V 0.84/6V

Teflon Bushing



### MINI/STD/JR

#### SPECIFICATION

Size(mm) : 35.0(L) x 16.9(W) x 27.0(H)

Weight(g) : 24.0

Speed(sec/60) : 0.14/4.8V 0.11/6V

Torque(kg-cm) : 3.60/4.8V 4.40/6V

Teflon Bushing



### S03TXF/STD/JR

#### SPECIFICATION

Size(mm) : 39.5(L) x 20.0(W) x 39.5(H) Weight(g) : 46.0

Speed(sec/60) : 0.21/4.8V 0.17/6V

Torque(kg-cm) : 5.00/4.8V 6.20/6V

Oiliness Bearing



### S04/BB/JR

#### SPECIFICATION

Size(mm) : 54.4(L) x 26.5(W) x 51.5(H) Weight(g) : 110.0

Speed(sec/60) : 0.25/4.8V 0.20/6V

Torque(kg-cm) : 10.00/4.8V 13.00/6V

1 Ball Bearings



## S11FHP/2BB/J

### SPECIFICATION

Size(mm) : 43.2(L) x 21.5(W) x 21.8(H) Weight(g) : 30.0

Speed(sec/60) : 0.15/4.8V 0.12/6V

Torque(kg-cm) : 4.80/4.8V 5.40/6V

2Ball Bearings



## S15CLN/2BBMG

### SPECIFICATION

Size(mm) : 40.5(L) x 20.0(W) x 37.5(H) Weight(g) : 66.4

Speed(sec/60) : 0.16/4.8V 0.13/6V

Torque(kg-cm) : 7.80/4.8V 9.20/6V

2Ball Bearings



## S666N/2BBMG

### SPECIFICATION

Size(mm) : 63.0(L) x 32.0(W) x 61.6(H) Weight(g) : 180.0

Speed(sec/60) : 0.22/4.8V 0.18/6V

Torque(kg-cm) : 18.00/4.8V 22.00/6V

2 Ball Bearings

