

ST-60/ST-80/ST-100

Digital Soldering Station



Features:

- 60W, 80W, 100W, soldering station with LCD display.
- ST-60 and ST-80 use ceramic heater.
- ST-100 use silver alloy heater, fast thermal conductivity.
- 3 sets shortcut temperature to simplify operations.
- Support temp lock, temp calibration function.
- Support °C and °F switchable.
- Smart standby and shutdown function, conserves energy and protect equipment.

Specification:

Product pictures			
Item No	ST-60	ST-80	ST-100
Voltage	AC(100V/110V/120V/220V/230V/240) 50/60Hz		
Power	60W	80W	100W
Temperature range	150°C~450°C	150°C~480°C	150°C~480°C
Temperature Stability	±2°C (in still air, no load)	±2°C (in still air, no load)	±2°C (in still air, no load)
The handle type	SP-60	SP-80	SP-100
Soldering tip type	T900-B	T900-B	T800-0.25I
Heater	60W dual-core ceramic heater HS-3060A	80W four-core ceramic heater HS-3080	100W Silver alloy heater HS-3100
Package list	Main unit: 1unit Handle set : 1 PCS Iron stand: 1 PCS Manual: 1 PCS AC cord: 1 PCS		
Standard Packing	Inner box: 315x270x152(mm) N.W.: 1.86kg G.W.: 2.2kg Carton: 6PCS/Carton Size: 555x330x480(mm) N.W.: 13.2kg G.W.: 14.3kg	Inner box: 315x270x152(mm) N.W.: 2.3kg G.W.: 2.64kg Carton: 6PCS/Carton Size: 555x330x480(mm) N.W.: 15.84kg G.W.: 16.94kg	Inner box: 315x270x152(mm) N.W.: 2.57kg G.W.: 2.91kg Carton: 6PCS/Carton Size: 555x330x480(mm) N.W.: 17.46kg G.W.: 18.56kg
Applications	<ul style="list-style-type: none"> • Institutes • Enterprises • Education and practice • Maintenance • Hobby 		

Note: T800 series soldering tip details in page 22.
T900 series soldering tip details in page 36.