

SV600 Acoustic Imager

Detect, locate and visualize the unheard and unseen

Visualize the unheard and the unseen with the power of acoustic imaging. The SV600 Fixed Acoustic Imager enables users to detect, locate and visualize air and gas leaks or changes in sound signatures across their process and equipment in real-time before they become costly problems.

By using an array of sophisticated sound sensors and powerful SoundMap[™] technology, the SV600 translates the sounds that it hears into a visual representation so that you can quickly locate problem areas. This provides facilities with further insights into product quality or safety concerns, as well as the ability to quickly detect changes across compressors, pumps, pipes and more.

In addition to 24/7 remote monitoring, the SV600 integrates into factory systems seamlessly and user-defined alarms can be established to alert users when sound signatures have changed, even in the parts of your facility that are hard to reach.

By serving as an early warning system, facilities can continuously monitor equipment to optimize performance, perform preventative maintenance or detect anomalies, such as bearing wear, well before a failure occurs to keep your processes up and running.



SV600 Fixed Acoustic Imager

Process and Asset Monitoring

Detect, locate and visualize sound signature changes across your process and equipment:

- Monitor equipment changes in real-time The SV600 continuously monitors your process for air and gas leaks, steam or vibrations and visually records any anomalies alerting users to areas of concern immediately.
- **Prevent unscheduled maintenance** Sound signatures are measurable well before any change in temperature can be detected. The SV600 can be used to find sound signature changes early on so facilities can schedule preventative maintenance and optimize performance before a failure occurs.
- Capture data from inaccessible locations The SV600 can be mounted close to any equipment or asset, to any area of the production line or where human access is restricted or dangerous.
- Continuous learning/improvement The SV600 can identify sound events, both relevant and irrelevant, and using a sophisticated algorithm, filters out bad sound events over time – improving users' overall detection rates.
- **Reduce power consumption** By quickly detecting and fixing air leaks, you can reduce your consumption of compressed air and energy to help save your facility money. Faulty, inefficient drive systems need to work harder, consuming additional power to stay operational.

On-Site Safety

Improve safety by continuously monitoring assets located in inaccessible areas, detecting new sound events in a critical factory location, or finding and visualizing escaping gases from fixed equipment.

- Minimize human intervention Improve workers' safety overall with a fully integrated, automated solution.
- Monitor assets and workspaces 24/7 Continuously monitor assets in hazardous or inaccessible locations at a safe distance, receive immediate alarms for new sound events or detect escaping gases from fixed equipment.
- **Reduce noise exposure** The SV600 includes user-programmable alarms for sound level (dB) and frequency (kHz) to help facilities better meet national and international standards and ensure workers are not exposed to dangerous noise and sound levels.

Inspections

Detect, locate and visualize sound signature changes across product inspection and quality control processes:

- **Intelligent leak detection** Using factory integration and real-time alarm features, the SV600 can automate acoustic detection on the production line and immediately notify your team of any quality issues or product rejects, improving productivity.
- Minimize operator intervention As a fixed, automated solution that integrates with your process, the SV600 eliminates the need for the constant operator intervention required of handheld sniffers, soap and water tests, manual audible methods or portable acoustic devices.
- Capture data from inaccessible locations The SV600 can be mounted close to any equipment or asset, to any area of the production line or where human access is restricted or dangerous.
- Automate product inspections The SV600 can be fully integrated with the factory system, supporting improved automation and efficiency and allowing users to automate their product inspections. With a fully digitized process, data can be recorded and archived to enable improved product traceability.

Front View



Ease of installation via RJ45 connector or M12 8 Pin connection and Vesa 10 mounting







Spot What You've Been Missing

The SV600 can also be used as a payload for Boston Dynamics' agile mobile robot $Spot^{\mathbb{B}}$.

Spot takes inspection to the next level. Designed to go where other robots can't go and to perform a broad number of tasks, Spot traverses unstructured terrain to automate industrial inspections, monitor remote or hazardous environments and provide situational awareness in remote settings.

The robot can also be reconfigured for various use cases to increase efficiency and greatly reduce safety risks. With the SV600 payload Spot will now be able to automate air and gas leak detection and identify sound signatures, all while on the go.



Model Overview

SV600-1 Standard Model plus

Standard Model plus VIS camera

SV600-BD

Payload for Boston Dynamics Spot® Robot Includes:

- SV600-1 Sonic Viewer
- Protective Metal Frame to mount on Spot
- Connection Cable to Spot

System Setup









Specifications

	SV600	
Physical Properties		
Dimensions (LxWxD)	170 x 170 x 65 mm (6.69 x 6.69 x 2.56 inch)	
Weight	0.85 kg (1.7 lb)	
Communication + Power	PoE IEEE 802.3af SV600-1 Connected via RJ45 or M12 8-Pin; IEEE 802.3 Status LED	SV600-1-0 = M12 8 Pin SV600-1-1 = RJ45
System Integration		
Event Triggering/Alarming	Set alarm levels for sound level (dB) and frequency (kHz) range	
Event Actions	Recording to external PC as .csv or .txt file	
Camera		
Integrated Visible Light	Included with fixed lens	
Resolution Video	640 x 480	
Camera Field of View	65° ±3°	
Camera Resolution	720 p at 30 fps	
Microphones		
Туре	MEMS, Digital Bottom Port	
SNR (A-weighted, at 1 kHz)	64 dB for 94 dB SPL @ 1kHz	
Sensitivity	-26 dB FS ± 1.5 dB at 1 kHz, 94 dB SPL	
Acoustic Overload Point	120 dB SPL at 1 kHz, <10 % THD	
General		
Ingress Protection	IP54	
Operating Temperatures	-20 °C to 50 °C (4 °F to 122 °F)	
Compliance		
FCC	Title47.Part 15	
EMC	EN55032:2015 EN61000-4-2:2009 EN61000-4-3:2006 EN61000-4-4:2012 EN61000-4-5:2006 EN61000-4-6:2009 EN61010-1:2010	
Data Formats		
Audio	.wav (audio verification)	
Pictures	.jpg, .png	
Video (V/V+ models)	.mjpeg, .mp4	
Data messages	.json	

Fluke Process Instruments

Americas

Everett, WA USA Tel: +1 800 227 8074 (USA and Canada, only) +1 425 446 6300 solutions@flukeprocessinstruments.com

EMEA

Berlin, Germany Tel: +49 30 4 78 00 80 info@flukeprocessinstruments.de

China

China Beijing, China Tel: +8610 6438 4691 info@flukeprocessinstruments.cn

Japan

Tokyo, Japan Tel: +81 03 6714 3114 info@flukeprocessinstruments.jp

Asia East and South India Tel: +91 22 6249 5028 Singapore Tel: +65 6799 5578 sales.asia@flukeprocessinstruments.com

Worldwide Service

Fluke Process Instruments offers services, including repair and calibration. For more information, contact your local office.

www.flukeprocessinstruments.com

© 2022 Fluke Process Instruments Specifications subject to change without notice. 5/2022 SV600_DS_RevA_EN