








Plug and Receptacle Mating View

Pin	Signal	Mating Sequence	Pin	Signal	Mating Sequence
A1	GND	First	B12	GND	First
A2	SSTXp1	Second	B11	SSRXp1	Second
A3	SSTXn1	Second	B10	SSRXn1	Second
A4	Vbus	First	B9	Vbus	First
A5	CC1	Second	B8	SBU2	Second
A6	Dp1	Second	B7	Dn2	Second
A7	Dn1	Second	B6	Dp2	Second
A8	SBU1	Second	B5	CC2	Second
A9	Vbus	First	B4	Vbus	First
A10	SSRXn2	Second	B3	SSTXn2	Second
A11	SSRXp2	Second	B2	SSTXp2	Second
A12	GND	First	B1	GND	First
SHELL	GND		SHELL	GND	

Specifications

Material

Insulator: LCP, UL 94V-0, Black
Contact: Copper Alloy, T=0.12mm
Mid Plate: Stainless Steel, T=0.20mm
EMI Plate: Stainless Steel, T=0.10mm
Shell: Stainless Steel, T=0.30mm

Plating

Contact
Contact Area: 3u" Au over 50µ" min. Nickel
Solder Tails: Gold Flash over 50µ" min. Nickel
Shell: 30µ" min. Nickel
Mid Plate: 50µ" min Sn over 30µ" min. Nickel
EMI Plate: Clear

Electrical

Current Rating: 5.00A collectively for Vbus pins
6.25A collectively for GND pins
1.25A for A5/B5 pin
0.25A per pin for all other pins

Voltage Rating: 48V DC

Power Rating: 240W

Contact Resistance: 40mΩ max initial.
50mΩ max after test

Dielectric Withstanding Voltage: 100V AC
Insulation Resistance 100MΩ min

Mechanical & Environmental

Operating Temperature: -25°C to +85°C

Mating Force: 5 to 20 N.

Unmated Force: 6 to 20 N after test

Durability: 20,000 cycles


Ordering Grid

USB4080-03-A Request Samples and Quotation

Contact Plating
03 = 3µ" Gold


Packing Options
A = Tape & Reel
(900pcs/Reel)

Part Number USB4080			Product Description USB3.2 Gen 2 Type C Receptacle, Dual Row SMT, Horizontal, PCB Top Mount			 www.gct.co	
Drawing Date 7th May 2021							
By KY		Tolerances (Except as Noted) Length X: ± 0.38 X.X ± 0.30 X.XX ± 0.15 X.XXX ± 0.10	Units: Metric (mm)	This drawing is confidential and copyright of Global Connector Technology, Ltd (GCT). This drawing must not be copied or disclosed without written consent. E & OE			
Detail Drawing Release		X: ±2° X.X ±1°	 3rd Angle Projection				
Revision A4	Date 14/10/24				Not to Scale	Drawn By CC	Sheet No. 1/3



Recommended PCB Layout
As viewed from component side Tolerance: $\pm 0.05\text{mm}$


■ Solder Area □ Component Outline





Recommended Solder mask
Thickness = 0.12mm
Tolerance: $\pm 0.05\text{mm}$

Part Number		Product Description	
USB4080		USB3.2 Gen 2 Type C Receptacle, Dual Row SMT, Horizontal, PCB Top Mount	
Drawing Date			
7th May 2021			
By	KY	Tolerances (Except as Noted)	Units:
Detail	Drawing Release	Length	Metric (mm)
Revision	A4	Angle	
Date	14/10/24		
		This drawing is confidential and copyright of Global Connector Technology, Ltd (GCT). This drawing must not be copied or disclosed without written consent. E & OE	
		Not to Scale	Drawn By CC
		Sheet No. 2/3	


GCT
www.gct.co



Direction of Unreeling



Direction of Unreeling



Pcs / Reel	Reels / Carton	Total Quantity
900	10	9000 pcs

Part Number USB4080		Product Description USB3.2 Gen 2 Type C Receptacle, Dual Row SMT, Horizontal, PCB Top Mount	
Drawing Date 7th May 2021			
By KY	Tolerances (Except as Noted) Length	Units: Metric (mm)	 This drawing is confidential and copyright of Global Connector Technology, Ltd (GCT). This drawing must not be copied or disclosed without written consent. E & OE
Detail Drawing Release	Angle		
Revision A4			
Date 14/10/24			
		3rd Angle Projection	 www.gct.co
			Not to Scale Drawn By CC Sheet No. 3/3