

1		2		3		4		5		6		7		
E											SIGN	DATE	DESCRIPTION	APPROVER
D														
C														
B														
A														

P.C.B. LAYOUT

N= Number of concats

材质于电镀/*Material*

塑件/*Insulator body*: PA66, UL94V-0

焊针/*Pin header*: Brass ,Tin planted

电器性能/*Electrical*

参考标准/ <i>Standard</i> :	UL	IEC
额定电压/ <i>Rated voltage</i> :	300V	250V
额定电流/ <i>Rated current</i> :	8A	10A
接触电阻/ <i>Contact resistance</i> :	20m Ω (max)	
绝缘电阻/ <i>Insulation resistance</i> :	500M Ω /500V	
耐电压/ <i>Withstanding voltage</i> :	AC 2000V/1Min	

机械性能/*Mechanical*

温度范围/ <i>Temperature range</i> :	-40°C to +105°C
瞬间温度/ <i>Max soldering</i> :	+250°C, for 5 Sec

尺寸/*Dimensions*

间距/ <i>Pitch</i> :	3.5mm
极数/ <i>Poles</i> :	2-24P

慈溪万海电子有限公司

CIXI WANHAI ELECTRONICS CO., LTD.

PART NAME: 15EDGRC-3.50-XXP				TITLE:	
PART NO.:				DWG NAME:	
APPROVED BY	CHECKED BY	DESIGNED BY	DRAWN BY	CUSTOM NO.:	Tolerance X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
					UNITS: mm
					SCALE: 4/1
					REVISION: 1