


WIMA Radial Lead Film Capacitors



MKP2 SE RIES MET ALI ZED POLYPROPYLENE

RoHS Compliant This product is RoHS compliant.



Specifications:

- Temperature Range: -55°C to +100°C
- Dielectric: Polypropylene film
- Capacitor Electrodes: Metalized plastic film
- Encapsulation: Flame retardant plastic case, 0 UL94V-

Features:

- For high frequency applications
- Suited for "sample & hold" circuits
- Stable negative TC
- Low ESR

For quantities greater than listed, call for quote.


Wima Part No.	Volts (Vdc/Vac)	Value (µF)	Tol. ±	Dimensions: in.			Lead Spacing (mm)
				W	H	L	
MKP2 0.01/100/5	100/63	0.01	5%	2.5	6.5	7.2	5.0
MKP2 0.022/100/5	100/63	0.022	5%	3	7.5	7.2	5.0
MKP2 0.033/100/5	100/63	0.033	5%	3	7.5	7.2	5.0
MKP2 0.047/100/5	100/63	0.047	5%	3.5	8.5	7.2	5.0
MKP2 0.1/100/5	100/63	0.1	5%	5	10	7.2	5.0
MKP2-1/100/10	100/63	0.1	10%	5	10	7.2	5.0
MKP2 0.15/100/5	100/63	0.15	5%	7.2	13	7.2	5.0
MKP2 0.22/100/5	100/63	0.22	5%	7.2	13	7.2	5.0
MKP2 0.33/100/5	100/63	0.33	5%	8.5	14	7.2	5.0
MKP2 0.01/250/5	250/160	0.01	5%	2.5	6.5	7.2	5.0
MKP2 0.022/250/5	250/160	0.022	5%	3	7.5	7.2	5.0
MKP2 0.033/250/5	250/160	0.033	5%	3	7.5	7.2	5.0
MKP20.047/250/5	250/160	0.047	5%	3.5	7.5	7.2	5.0
MKP20.1/250/5	250/160	0.1	5%	5	10	7.2	5.0
MKP2 0.22/250/5	250/160	0.22	5%	7.2	13	7.2	5.0
MKP2 0.33/250/5	250/160	0.33	5%	8.5	14	7.2	5.0
MKP20.01/400/5	400/200	0.01	5%	3.5	8.5	7.2	5.0
MKP2 1000/630/10	630/250	0.001	10%	2.5	6.5	7.2	5.0
MKP24700/630/5	630/250	0.0047	5%	3	7.5	7.2	5.0

Film Capacitors

Wima



MKS2 SE RIES MET ALI ZED POLYESTER



Specifications:

- Temperature Range: -55°C to +100°C
- Dielectric: Polyethylene-terephthalate film
- Capacitor Electrodes: Metalized plastic film
- Encapsulation: Flame retardant vacuum-deposited aluminum


Features:

- Reservoir capacitor with unlimited life at high temperatures
- Ideally suited for wide temperature range applications

MKS2-1/50/10	50/30	1.0	10%	3.5	8.5	7.2	5.0
MKS2-1.5/50/10	50/30	1.5	10%	4.5	9.5	7.2	5.0
MKS2-2.2/50/10	50/30	2.2	5%	5.0	10.0	7.2	5.0
MKS2-2.2/50/10	50/30	2.2	10%	5	10	7.2	5.0
MKS2-3.3/50/10	50/30	3.3	10%	5.5	11.5	7.2	5.0
MKS2-4.7/50/10	50/30	4.7	10%	7.2	13	7.2	5.0
MKS2-01/63/10	63/40	0.01	10%	2.5	6.5	7.2	5.0
MKS20-01/63/5	63/40	0.01	5%	2.5	6.5	7.2	5.0
MKS2-022/63/10	63/40	0.022	10%	2.5	6.5	7.2	5.0
MKS20-022/63/5	63/40	0.022	5%	2.5	6.5	7.2	5.0
MKS20-033/63/10	63/40	0.033	10%	2.5	6.5	7.2	5.0
MKS20-047/63/10	63/40	0.047	10%	2.5	6.5	7.2	5.0
MKS20-047/63/5	63/40	0.047	5%	2.5	6.5	7.2	5.0
MKS20-068/63/10	63/40	0.068	10%	2.5	6.5	7.2	5.0
MKS20-068/63/5	63/40	0.068	5%	2.5	6.5	7.2	5.0
MKS2-1/63/10	63/40	0.1	10%	2.5	6.5	7.2	5.0
MKS2-1/63/5	63/40	0.1	5%	2.5	6.5	7.2	5.0
MKS2-15/63/5	63/40	0.15	5%	2.5	6.5	7.2	5.0
MKS2-15/63/10	63/40	0.15	10%	2.5	6.5	7.2	5.0
MKS20-22/63/10	63/40	0.22	10%	3	7.5	7.2	5.0
MKS20-22/63/5	63/40	0.22	5%	3	7.5	7.2	5.0
MKS2-33/63/5	63/40	0.33	5%	3.5	8.5	7.2	5.0
MKS2-33/63/10	63/40	0.33	10%	3.5	8.5	7.2	5.0
MKS2-47/63/10	63/40	0.47	10%	4.5	9.5	7.2	5.0
MKS20-47/63/5	63/40	0.47	5%	4.5	9.5	7.2	5.0
MKS2-68/63/10	63/40	0.68	10%	4.5	9.5	7.2	5.0
MKS2-1.0/63/10	63/40	1.0	10%	5	10	7.2	5.0
MKS2-1.0/63/5	63/40	1.0	5%	5	10	7.2	5.0
MKS2-1.5/63/5	63/40	1.5	5%	5.5	11.5	7.2	5.0
MKS2-2.2/63/5	63/40	2.2	5%	7.2	13.0	7.2	5.0
MKS2-01/100/5	100/63	0.01	5%	2.5	6.5	7.2	5.0
MKS2-01/100/10	100/63	0.01	10%	2.5	6.5	7.2	5.0
MKS2-1/100/10	100/63	0.1	10%	3	7.5	7.2	5.0
MKS2-22/100/10	100/63	0.22	10%	3.5	8.5	7.2	5.0
MKS2-1/100/10	100/63	1.0	10%	7.2	13.0	7.2	5.0



FKP 2 SE RIES FILM/FOIL POLYPROPYLENE



Specifications:

- Temperature Range: -55°C to +100°C
- Dielectric: Polypropylene film
- Capacitor Electrodes: Metal foil film
- Encapsulation: Flame retardant plastic case, 0 UL94V-

Features:

- Pulse applications with high repetition frequency
- Suited for replacement of polystyrene capacitors in and HF audio applications.

FKP2-4700/63/2.5	63/40	0.0047	2.5%	4.5	6	7.2	5.0
FKP2-6800/63/2.5	63/40	0.0068	2.5%	4.5	6.0	7.2	5.0
FKP2-01/63/5	63/40	0.01	5.0%	5.5	7	7.2	5.0
FKP2-01/63/2.5	63/40	0.01	2.5%	5.5	7	7.2	5.0
FKP2-01/63/1	63/40	0.01	1.0%	5.5	7	7.2	5.0
FKP2-022/63/2.5	63/40	0.022	2.5%	7.2	8.5	7.2	5.0
FKP2-100/100/2.5	100/63	100pF	2.5%	4.5	6.0	7.2	5.0
FKP2-100/100/5	100/63	100pF	5.0%	4.5	6	7.2	5.0
FKP2-150/100/2.5	100/63	150pF	2.5%	4.5	6	7.2	5.0
FKP2-220/100/2.5	100/63	220pF	2.5%	4.5	6	7.2	5.0
FKP2-330/100/5	100/63	330pF	5.0%	4.5	6	7.2	5.0
FKP2-470/100/2.5	100/63	470pF	2.5%	4.5	6	7.2	5.0
FKP2-470/100/5	100/63	470pF	5%	4.5	6.0	7.2	5.0
FKP2-680/100/2.5	100/63	680pF	2.5%	4.5	6	7.2	5.0
FKP2-1000/100/5	100/63	0.001	5.0%	4.5	6	7.2	5.0
FKP2-1000/100/2.5	100/63	0.001	2.5%	4.5	6	7.2	5.0
FKP2-1500/100/2.5	100/63	0.0015	2.5%	4.5	6	7.2	5.0
FKP2-2200/100/2.5	100/63	0.0022	2.5%	4.5	6	7.2	5.0
FKP2-2200/100/5	100/63	0.0022	5%	4.5	6.0	7.2	5.0
FKP2-3300/100/2.5	100/63	0.0033	2.5%	5.5	7.0	7.2	5.0
FKP2-4700/100/2.5	100/63	0.0047	2.5%	5.5	7	7.2	5.0
FKP2-01/100/2.5	100/63	0.01	2.5%	6.5	8	7.2	5.0
FKP2-470/250/5	250/160	470pF	5%	4.5	6.0	7.2	5.0