



Fuse-link, high speed, 16 A, AC 240 V, DC 150 V, BS88, 18 x 56 mm, aR, BS



Part no. 16A 240V AC TYPE T FUSE (10)
16LET

General specifications		
Product name		Eaton Bussmann series high speed british standard fuse
Part no.		16A 240V AC TYPE T FUSE (10)
EAN		5027590437660
Product Length/Depth		55 millimetre
Product height		18 millimetre
Product width		18 millimetre
Product weight		32 gram
Compliances		RoHS Compliant CE Marked
Product Tradename		None
Product Type		High speed british standard fuse
Product Sub Type		None
Electrical data		
Amperage Rating		16 A
Voltage rating		280 V
Rated voltage AC		280 V
Rated voltage DC		150 V
Interrupt rating		200 kA RMS Sym, 50 kA DC at 150 Vdc
Class		Class aR
Clearing (I2T)		70 at 120 V, 140 at 240 V
Watt losses		2.5 W
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse indicator		None
Compatible Trip indicator/microswitch		
Suitable for		TI500 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecI@ss13-27-14-20-90 [BAB264016])			
Fuse system according to IEC 60269			Other
Fuse construction type according to IEC 60269			Other
Type of current			AC/DC
Rated voltage AC		V	280
Rated voltage DC		V	150
Rated current		A	16
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	200
Colour code			None
Type of fuse status indicator			None
Power loss at rated current		W	2.5
Mounting holes			M6
Centre-to-centre distance of connections		mm	41.5