

1

2

3

4

5

Specifications:

Current Rating: 2.0A AC,DC

Voltage Rating: 250V AC,DC

Contact Resistance: 20m ohm.Max

Insulation Resistance: 1000M ohm.Min

Withstanding Voltage: 500V AC/Minute

Operating Temperature Range: -40°C ~ +105°C

Material And Finish:

Insulator: Nylon 9T (UL94V-0)

Insulator Color: Black

Contact: Phosphor Bronze

Plated: Gold/Tin/Selective Gold Plated $\triangle B$

How To Order

2207S-XXX

G:Gold Plated

T: Tin Plated

SG: Selective Gold Plated $\triangle B$

No. Of Contacts

Straight Type

Dimension :

Pin.No	Dim.A	Dim.B	Pin.No	Dim.A	Dim.B	Pin.No	Dim.A	Dim.B	Pin.No	Dim.A	Dim.B
04	4.50	2.00	24	24.50	22.00	44	44.50	42.00	64	64.50	62.00
06	6.50	4.00	26	26.50	24.00	46	46.50	44.00	66	66.50	64.00
08	8.50	6.00	28	28.50	26.00	48	48.50	46.00	68	68.50	66.00
10	10.50	8.00	30	30.50	28.00	50	50.50	48.00	70	70.50	68.00
12	12.50	10.00	32	32.50	30.00	52	52.50	50.00	72	72.50	70.00
14	14.50	12.00	34	34.50	32.00	54	54.50	52.00	74	74.50	72.00
16	16.50	14.00	36	36.50	34.00	56	56.50	54.00	76	76.50	74.00
18	18.50	16.00	38	38.50	36.00	58	58.50	56.00	78	78.50	76.00
20	20.50	18.00	40	40.50	38.00	60	60.50	58.00	80	80.50	78.00
22	22.50	20.00	42	42.50	40.00	62	62.50	60.00			

P.C.B Layout

RoHS Compliant

F				DRAWN: CHERRY	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15	Neltron Industrial Co., Ltd.	DESCRIPTION: 2.0mm PCB Socket Double Row Straight Type	SIZE A4
E								
D				CHECKED: DENNIS	UNIT: MM	PART NO: 2207S-XXX		
C								SCALE: 1:1
B	21-MAR-2022	Add Plated	MEI	APPROVAL: CHERRY	SHEET: 1/1			
A	30-JUL-2013	(P0001)	CHERRY			PROJECTION:		
REV	DATE	FILE	BY	MIKE				