

RoHS COMPLIANT

REV	ECN NO.	DESCRIPTION	DATE
A		RELEASE	JAN. 09'01
B		REDRAW	NOV. 18'08
C		MODIFY P/N	MAR. 31'11

SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 7A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000M Ω min
- Temperature Range : - 25 $^{\circ}$ C to + 85 $^{\circ}$ C
- Contact Resistance : 20m Ω max

HOUSING

- Poles : 2-14
- Material : Nylon 66 UL94V-2
- Q' ty : 1,000 pcs./Bag

Poles	Dimensions(mm)	
	A	B
2	3.96	8.92
3	7.92	12.88
4	11.88	16.84
5	15.84	20.80
6	19.80	24.76
7	23.76	28.72
8	27.72	32.68
9	31.68	36.64
10	35.64	40.60
11	39.60	44.56
12	43.56	48.52
13	47.52	52.48
14	51.48	56.44

TOLERANCE UNLESS OTHERWISE SPECIFIED			PROJECTION		GOLD-TEK ELECTRIC CO., LTD.		
LINEAR		ANGLE	UNITS	MM	TITLE	PART NO.	
X. ±	X°. ±						
.X ± 0.38	.X°. ±				3.96mm Housing	5001**	
.XX ± 0.25	.XX°. ±						
.XXX±	.XXX°. ±		SCALE		CPART NO.	SHEET	
APPD			1 OF 1				
CHKD			SIZE		圖面編號:GTKSD0607-C(1)		
DRAW	Z	MAR. 31'2011	A4				

圖面編號:GTKSD0607-C(1)