




Functional Characteristics 電氣特性

Testing current 測試電流	Blow time limit 熔斷時間	
	Min 最小	Max 最大
100%	4 hour (小時)	-
135%	-	1 hour (小時)
200% (100mA – 15A)	5 sec (秒)	30 sec (秒)
200% (20A – 30A)	3 sec (秒)	30 sec (秒)

Safety Approvals (安全認證)

UL listed and CSA certified from 100mA to 10A at 125/250V. 6H 12A to 30A, and 6HP 12A to 25A, 125/250V are UL recognized and CSA component accepted.

Marking (印字)

Sun trademark, appropriate UL/CSA logo, "6H", current and voltage ratings are stamped on the fuse end caps.

Material (材料)


Fuse body – ceramic tube
End cap – nickel plated brass
Pigtail – tin plated copper on nickel plated brass cap

Packing (包裝)

Bulk pack of 500pcs per box for 6H and 250pcs for 6HP.

RoHS

Comply with EU Directive 2011/65/EU.



Reference Information 參考資料

Current Rating 額定電流 (A)	Voltage Rating 額定電壓 (V)	Avg Cold Resistance 平均電阻 (ohm)	Avg V - drop 平均電壓降 (V)	Avg Power Dissipation 平均消耗功率 (W)	Average I ² t value 熔化熱能 (A ² sec)
0.100	250	32	4.1	0.45	0.03
0.125	250	23	3.8	0.52	0.04
0.160	250	14	3.0	0.52	0.10
0.200	250	8.5	2.3	0.52	0.17
0.250	250	5.8	2.0	0.55	0.21
0.300	250	4.2	1.8	0.59	0.39
0.375	250	2.8	1.5	0.61	0.59
0.500	250	1.6	1.1	0.62	1.8
0.750	250	0.73	0.77	0.64	5.2
1.0	250	0.45	0.63	0.69	6.7
1.25	250	0.29	0.51	0.70	14
1.6	250	0.19	0.40	0.71	26
2	250	0.12	0.34	0.75	41
2.5	250	0.085	0.29	0.80	67
3.0	250	0.063	0.27	0.89	101
4	250	0.038	0.22	0.97	170
5	250	0.028	0.21	1.16	246
6.0	250	0.023	0.20	1.32	369
7.0	250	0.019	0.20	1.54	521
8	250	0.016	0.19	1.67	709
10	250	0.012	0.19	2.02	925
12	250	0.008	0.12	1.58	679
15	250	0.006	0.11	1.82	1260
20	250	0.004	0.11	2.32	3020
25	250	0.003	0.11	3.03	4281
30	250	0.0023	0.10	4.10	5227

Note (備注):

- The Voltage Drop values are measured at 100% rated current.
- The Power Dissipation values are measured after 1 hour of testing at 100% rated current.
- The above figures are typical values for reference only and should not be used as acceptance criteria.
- Please consult factory for availability of other ratings.

Specifications subject to change without notice