

CONVERTER LIST - ALL-100 Family

[Download](#)

| PACKAGE | CONVERTER | Function |
|-------------|------------------|--|
| BGA | CNV-BGA-DIP8 | 8-pin BGA(PITCH 0.75mm,3.73x2.35mm,4x2 Grid) socket. Supports ATMEL AT24C512C.(8-pin VFBGA) |
| BGA | CNV-SPIA-BG24 | 24-pin BGA(PITCH 1.0mm,8x6mm,6x4 Grid) socket. Supports 24-ball BGA serial PROM. |
| DIP | CNV-DIP-35LV020 | 32-pin DIP socket. Supports GTK ARF35LV020. |
| DIP | CNV-DIP48-78E354 | 48-pin DIP socket. Supports WINBOND W78E354. |
| DIP | CNV-DIP-EPC | 32-pin DIP socket. Supports ALTERA EPC1. |
| DIP | CNV-DIP-XC17SXX | 32-pin DIP socket. Supports XILINX XC17S200A.(8-pin DIP) |
| MEMORY CARD | CNV-SD11-DIP10 | MMC card socket. Supports ATMEL AT45DCB002.(7-pin DataFlash Card) |

| | | |
|------|-------------------|---|
| PLCC | CNV-PL44-COP8SAX | 44-pin PLCC socket. Supports NATIONAL COP8SAC744V,COP8SGE744V, COP8SACGR744V. |
| PLCC | CNV-PL44-COP8X9 | 44-pin PLCC socket. Supports NATIONAL COP8CBR9,COP8CDR9. |
| PLCC | CNV-PL44-COP8X9V2 | 44-pin PLCC socket. Supports NATIONAL COP8CBR9,COP8CCR9,COP8CDR9, COP8SBR9,COP8SCR9,COP8SDR9. |
| PLCC | CNV-PL44-COPL8RB | 44-pin PLCC socket. Supports NATIONAL COP87L88RBV. |
| PLCC | CNV-PL52-TSC51I2 | 52-pin PLCC socket. Supports TEMIC TSC8751I2,TSC8751C3. |
| PLCC | CNV-PL68-51RD2 | 68-pin PLCC socket. Supports TEMIC T89C51RD2. |
| PLCC | CNV-PL68-COP8X9 | 68-pin PLCC socket. Supports NATIONAL COP8SXX9/CXX9. |
| PLCC | CNV-PLCC-16C64B | 44-pin PLCC socket. Supports MICROCHIP PIC16C64/65,PIC16C74. |

PLCC CNV-PLCC-17C42 44-pin PLCC socket.
Supports MICROCHIP PIC17C42/43/44.

PLCC CNV-PLCC-35LV020 32-pin PLCC socket.
Supports GTK ARF35LV020.

PLCC CNV-PLCC-78E354 68-pin PLCC socket.
Supports WINBOND W78E354.

PLCC CNV-PLCC-87251A1 44-pin PLCC socket.
Supports TEMIC TSC87251A1.

PLCC CNV-PLCC-90S8535 44-pin PLCC socket.
Supports ATMEL AT90S8535,AT90S4434.

PLCC CNV-PLCC-AT17XXA 20-pin PLCC socket.
Supports ATMEL AT17C128A.

PLCC CNV-PLCC-ATV2500 44-pin PLCC socket.
Supports ATMEL ATV2500H/L/LV/LVL/B/BL/BQ/BQL;
PHILIPS PLV2500.

PLCC CNV-PLCC-DIP28 28-pin PLCC socket.
Supports pin to pin,DIP-28 to PLCC-28.

| | | |
|------|------------------|--|
| PLCC | CNV-PLCC-EP1M32A | <p>32-pin PLCC socket.</p> <p>Supports all 32-pin PLCC EPROM from 1MB up, 28F020,28F010,28F512,28F256,29F010,29F040.</p> |
| PLCC | CNV-PLCC-EP1M44 | <p>44-pin PLCC socket.</p> <p>Supports all 44-pin PLCC EPROM from 1MB up.</p> <p>The pins not connected are: 1,13,23,33.</p> |
| PLCC | CNV-PLCC-EP512 | <p>32-pin PLCC socket.</p> <p>Supports all 32-pin PLCC EPROM ranging from 2764 to 27512.</p> <p>The pins not connected are: 1,12,17,26.</p> |
| PLCC | CNV-PLCC-EP610 | <p>28-pin PLCC socket.</p> <p>Supports ALTERA EP600/610/630,EP600I/610I,85C060; AMD PLACE610H; INTEL 5C060,85C060,iPLD610; TI EP610/630.</p> |
| PLCC | CNV-PLCC-EP910 | <p>44-pin PLCC socket.</p> <p>Supports ALTERA EP910I,85C090,EP900/910/910A/900I; INTEL 5C090,85C090,iPLD910; TI EP910.</p> |

| | | |
|------|------------------|--|
| PLCC | CNV-PLCC-EPC1213 | 20-pin PLCC socket. Supports ALTERA EPC1,EPC1064,EPC1064V,EPC1213,EPC1441. |
| PLCC | CNV-PLCC-EPC2 | 20-pin PLCC socket. Supports ALTERA EPC2LC20. |
| PLCC | CNV-PLCC-EPM5032 | 28-pin PLCC socket. Supports ALTERA EPM5032; CYPRESS CY7C344. |
| PLCC | CNV-PLCC-MPU51B | 44-pin PLCC socket. Supports MPU 8751/89C51 series,SST 89E564. (except PHILIPS 87C550; SIEMENS C513A-2E; INTEL 87L51FA/FB/FC/52/54/58) |
| PLCC | CNV-PLCC-PAL20 | 20-pin PLCC socket. Supports 20-pin PLCC PAL. |
| PLCC | CNV-PLCC-PAL28A | 28-pin PLCC socket. Supports 28-pin PLCC PAL. The pins not connected are: 1,8,15,22. |
| PLCC | CNV-PLCC-PAL28C | 28-pin PLCC socket. Supports ATMEL ATF22V10C,ATF22LV10C,ATF22V10CZ,ATF22LV10CZ. |

| | | |
|------|------------------|---|
| PLCC | CNV-PLCC-PROM28A | 28-pin PLCC socket. 27S47/49/180/181/280/281/190/191/290/291. The pins not connected are:1,10,15,21. |
| PLCC | CNV-PLCC-W78E378 | 44-pin PLCC socket. Supports WINBOND W78E378P. |
| PLCC | CNV-PLCC-XC1736 | 20-pin PLCC socket. Supports 20-pin PLCC serial EEPROM. XILINX XC1736,XC1736A,XC1765,XC17128,XC1718D, XC1736D,XC1765D,XC1718L,XC1736L,XC1765L. The pins not connected are:1,3,5,7,9,11,12,13,15,16,18,19. |
| PLCC | CNV-PLCC-XC17V16 | 44-pin PLCC socket. Supports XILINX XC17V16,XC17V08. |
| PLCC | CNV-PLCC-XC17VXX | 20-pin PLCC socket. Supports XILINX XC17V02. |
| PLCC | CNV-PLCC-XQ1701L | 44-pin PLCC socket. Supports XILINX XQ1701L. |
| PLCC | CNV-PLCC-Z86E21 | 44-pin PLCC socket. Supports ZILOG Z86E21. |

| | | |
|----------|---------------------------|---|
| QFN(MLF) | CNV-LLP44-COP8X9 | 44-pin QFN(PITCH 0.5mm,7x7mm,Array:12 on 2,10 on 2) socket. Supports NATIONAL COP8CB/CC/CDR9,COP8SB/SC/SDR9. (44-pin LLP) |
| QFN(MLF) | CNV-MLF20-HT82B40R | 20-pin QFN(PITCH 0.65mm,5x5mm,Array:5 on 4 + 1) socket. Supports HOLTEK HT82B40R. |
| QFN(MLF) | CNV-MLF28- PIC16C72AV2 | 28-pin QFN(PITCH 0.65mm,6x6mm,Array:7 on 4) socket. Supports MICROCHIP PIC16LF873A,PIC18F2431,PIC18F25J10. (28-pin MLF) |
| QFN(MLF) | CNV-MLF28-PIC16F88 | 28-pin QFN(PITCH 0.65mm,6x6mm,Array:7 on 4) socket. Supports MICROCHIP PIC16F81X series.(28-pin MLF) |
| QFN(MLF) | CNV-MLF-AT90PWM3 | 32-pin QFN(PITCH 0.65mm,7x7mm,Array:8 on 4 + 1) socket. Supports ATMEL AT90PWM3. |
| QFN(MLF) | CNV-MLF-ATTINY13A | 10-pin QFN(PITCH 0.5mm,3x3mm,Array:2 on 5 + 1) socket. Supports ATMEL ATTINY2313.(20-pin MLF) |
| QFN(MLF) | CNV-MLF-ATTINY2313 | 20-pin QFN(PITCH 0.5mm,4x4mm,Array:5 on 4 + 1) socket. Supports ATMEL ATTINY2313.(20-pin MLF) |
| QFN(MLF) | CNV-MLF-ATTINY26 | 32-pin QFN(PITCH 0.5mm,5x5mm,Array:8 on 4) socket. Supports ATMEL ATTINY26,ATTINY26L.(32-pin MLF) |

| | | |
|----------|-------------------|--|
| QFN(MLF) | CNV-MLF-ATTINY28A | 32-pin QFN(PITCH 0.5mm,5x5mm,Array:8 on 4 + 1) socket. Supports ATMEL ATTINY28,ATMEGA8L.(32-pin MLF) |
| QFN(MLF) | CNV-MLF-HT82K68E | 32-pin QFN(PITCH 0.5mm,5x5mm,Array:8 on 4 + 1) socket. Supports HOLTEK HT82K68E. |
| QFN(MLF) | CNV-MLF-MEGA162 | 44-pin QFN(PITCH 0.5mm,7x7mm,Array:11 on 4) socket. Supports ATMEL ATMEGA162.(44-pin MLF) |
| QFN(MLF) | CNV-MLF-MEGA8535 | 44-pin QFN(PITCH 0.5mm,7x7mm,Array:11 on 4) socket. Supports ATMEL ATMEGA8535.(44-pin MLF) |
| QFN(MLF) | CNV-QFN16-HCS08 | 16-pin QFN(PITCH 0.8mm,5x5mm,Array:4 on 4 + 1) socket. Supports FREESCALE,MOTOROLA MC9S08QG4CFFE, MC9S08QG8CFFE. |
| QFN(MLF) | CNV-QFN16-PICS | 16-pin QFN(PITCH 0.65mm,4x4mm,Array:4 on 4 + 1) socket. Supports MICROCHIP PIC16F684. |
| QFN(MLF) | CNV-QFN44-PICS | 44-pin QFN(PITCH 0.65mm,8x8mm,Array:11 on 4 + 1) socket. Supports MICROCHIP PIC16LF874A. |
| QFN(MLF) | CNV-QFN-DIP24 | 24-pin QFN(PITCH 0.5mm,4x4mm,Array:6 on 4 + 1) socket. Supports pin to pin,DIP-24 to QFN-24. |

| | | |
|-----|-----------------|--|
| QFP | CNV-PQFP-TS52X2 | 44-pin QFP(PITCH 0.8mm,10x10mm) socket. Supports TEMIC TS87C52X2.(44-pin PQFP) |
| QFP | CNV-Q44-COP8SAX | 44-pin QFP(PITCH 0.8mm,10x10mm) socket. Supports NATIONAL COP8SAC744VEJ,COP8SGE744VEJ, COP8SGR744VEJ.(44-pin PQFP) |
| QFP | CNV-Q64-51RD2 | 64-pin QFP(PITCH 0.5mm,10x10mm) socket. Supports TEMIC T89C51RD2.(64-pin TQFP) |
| QFP | CNV-QFP-16C64 | 44-pin QFP(PITCH 0.8mm,10x10mm) socket. Supports MICROCHIP PIC16C64,PIC16C65,PIC16C74. |
| QFP | CNV-QFP-17C42 | 44-pin QFP(PITCH 0.8mm,10x10mm) socket. Supports MICROCHIP PIC17C42/43/44. |
| QFP | CNV-QFP48-78E61 | 48-pin QFP(PITCH 0.5mm,7x7mm) socket. Supports WINBOND W78E512,W78E61. |
| QFP | CNV-QFP-90S4433 | 32-pin QFP(PITCH 0.8mm,7x7mm) socket. Supports ATMEL AT90S2333,AT90LS2333,AT90S4433,AT90LS4433. |
| QFP | CNV-QFP-90S8535 | 44-pin QFP(PITCH 0.8mm,10x10mm) socket. Supports ATMEL AT90S4434,AT90S8535. |

| | | |
|------|-----------------|--|
| QFP | CNV-QFP-AT17XXA | 32-pin QFP(PITCH 0.8mm,7x7mm) socket. Supports ATMEL AT17LV002A. |
| QFP | CNV-QFP-EPC2 | 32-pin QFP(PITCH 0.8mm,7x7mm) socket. Supports ALTERA EPC2TC32. |
| QFP | CNV-QFP-MPU51B | 44-pin QFP(PITCH 0.8mm,10x10mm) socket. Supports MPU 8751/89C51 series,SST 89E564. (except PHILIPS 87C550; SIEMENS C513A-2E; INTEL 87L51FA/FB/FC/52/54/58) |
| QFP | CNV-QFP-W77E468 | 100-pin QFP(PITCH 0.65mm,14x20mm) socket. Supports WINBOND W77E468. |
| QFP | CNV-QFP-XC17XX | 44-pin QFP(PITCH 0.8mm,10x10mm) socket. Supportss XILINX XC1702L,XC1704L. |
| SDIP | CNV-SDIP-DIP28 | 28-pin SDIP(PITCH 1.778mm,400mil) socket. Supports pin to pin,DIP-28 to SDIP-28. |
| SDIP | CNV-SDIP-DIP32 | 32-pin SDIP(PITCH 1.78mm,400mil) socket. Supports pin to pin,DIP-32 to SDIP-32. |

| | | |
|-----|------------------|---|
| SON | CNV-CASON-DIP8A | 8-pin SON(PITCH 1.27mm,6x8mm,Array:4 on 2) socket. Supports ATMEL AT45DBXX.(8-pin CASON); STM M25PXXX.(8-pin MLP) |
| SON | CNV-DFN-HCS08 | 8-pin SON(PITCH 0.8mm,4x4mm,Array:4 on 2 + 1) socket. Supports FREESCALE MC9S08QA2,MC9S08QG4.(8-pin DFN) |
| SON | CNV-MISON-DIP8 | 8-pin SON(PITCH 0.5mm,2x3mm,Array:4 on 2 + 1) socket. Supports MICROCHIP 24AA64,24LC64.(8-pin DFN) |
| SON | CNV-MISON-DIP8A3 | 8-pin SON(PITCH 0.5mm,2x3mm,Array:4 on 2 + 1) socket. Supports 8-pin SON serial PROM. |
| SON | CNV-SNT-DIP8 | 8-pin SON(PITCH 0.5mm,1.97x2.23mm,Array:4 on 2) socket. Supports SEIKO S-24C02BP.(8-pin SNT) |
| SON | CNV-TDFN-DIP8 | 8-pin SON(PITCH 0.65mm,3x3mm,Array:4 on 2 +) socket. Supports DALLAS,MAXIM MAX9660.(8-pin TDFN) |
| SOP | CNV-MSOP-DIP10 | 10-pin SOP(PITCH 0.5mm,3mm) socket. Supports HOLTEK HT46R01-1,HT46R02-1,HT46R03-1. (10-pin MSOP) |
| SOP | CNV-MSOP-DIP8 | 8-pin SOP(PITCH 0.65mm,3mm) socket. Supports MICROCHIP 24XX series.(8-pin MSOP) |

| | | |
|-----|-------------------|--|
| SOP | CNV-QSOP-DIP28B | 28-pin SOP(PITCH 0.635mm,3.94mm) socket. Supports CYPRESS PALCE16V8/L.(28-pin QSOP) |
| SOP | CNV-SOP-18F25J10 | 28-pin SOP(PITCH 1.27mm,7.6mm) socket. Supports MICROCHIP PIC18F26J50. |
| SOP | CNV-SOP-AT25HP512 | 28-pin SOP(PITCH 1.27mm,7.6mm) socket. Supports ATMEL AT25HP512.(16-pin SOP) |
| SOP | CNV-SOP-DIP28A | 28-pin SOP(PITCH 1.27mm,7.6mm) socket. Supports pin to pin,DIP-28 to SOP-28. |
| SOP | CNV-SOP-DIP28B | 28-pin SOP(PITCH 1.27mm,9mm) socket. Supports TOSHIBA TC54512AF. |
| SOP | CNV-SOP-DIP32 | 32-pin SOP(PITCH 1.27mm,7.55mm) socket. Supports ATMEL AT90PWM3; HAIER HR6P78P8S. |
| SOP | CNV-SOP-DIP40 | 40-pin SOP(PITCH 1.27mm,11.4mm) socket. Supports MXIC MX27C4100. |
| SOP | CNV-SOP-EP1M32 | 32-pin SOP(PITCH 1.27mm,11.6mm) socket. Supports all 32-pin SOP EPROM and EEPROM,from 1MB up. |

| | | |
|-----|-----------------|---|
| SOP | CNV-SOP-EP512 | 28-pin SOP(PITCH 1.27mm,8.45mm) socket. Supports 28-pin SOP EPROM from 2764 to 27512. |
| SOP | CNV-SOP-FS6370 | 16-pin SOP(PITCH 1.27mm,4.2mm) socket. Supports AMI FS6370-01. |
| SOP | CNV-SOP-NDIP16A | 16-pin SOP(PITCH 1.27mm,4.2mm) socket. Supports 14-pin SOP(150 mil) serial EEPROM. |
| SOP | CNV-SOP-NDIP16B | 24-pin SOP(PITCH 1.27mm,5.5mm) socket. Supports MICROCHIP 24C65.(8-pin SOP) |
| SOP | CNV-SOP-NDIP16C | 16-pin SOP(PITCH 1.27mm,4.2mm) socket. Supports ATMEL AT93C46/56/57/66(REVERSE). |
| SOP | CNV-SOP-NDIP16F | 16-pin SOP(PITCH 1.27mm,4.2mm) socket. Supports pin to pin,DIP-16 to SOP-16. |
| SOP | CNV-SOP-NDIP16G | 16-pin SOP(PITCH 1.27mm,3.9mm) socket. Supports pin to pin,DIP-16 to SOP-16. |
| SOP | CNV-SOP-NDIP16H | 24-pin SOP(PITCH 1.27mm,5.5mm) socket. Supports EXCELSEMI ES25P80.(8-pin SOP) |
| SOP | CNV-SOP-NDIP16I | 16-pin SOP(PITCH 1.27mm,3.9mm) socket. Supports 8-pin SOP(150 mil) serial PROM(REVERSE). |

| | | |
|-----|-------------------|---|
| SOP | CNV-SOP-NDIP8 | 8-pin SOP(PITCH 1.27mm,4.4mm) socket. Supports pin to pin,DIP-8 to SOP-8. |
| SOP | CNV-SOP-PIC16C5X | 28-pin SOP(PITCH 1.27mm,7.6mm) socket. Supports MICROCHIP PIC16C54,PIC16C55,PIC16C56, PIC16C57,PIC16C58,PIC16C71,PIC16C84/LC84. |
| SOP | CNV-SOP-SPI16A | 28-pin SOP(PITCH 1.27mm,7.6mm) socket. Supports STM M25PXXX.(16-pin SOP) |
| SOP | CNV-SOP-XC17XX | 28-pin SOP(PITCH 1.27mm,7.6mm) socket. Supports XILINX XC1701,XC1701/L,XC17512L. |
| SOP | CNV-SSOP-18F25J10 | 30-pin SOP(PITCH 0.65mm,5.7mm) socket. Supports MICROCHIP PIC18F25J10.(SSOP-28) |
| SOP | CNV-SSOP-87C5111 | 30-pin SOP(PITCH 0.65mm,5.7mm) socket. Supports ATMEL AT87C5111.(24-pin SSOP) |
| SOP | CNV-SSOP-DIP30A | 30-pin SOP(PITCH 0.65mm,5.7mm) socket. Supports pin to pin,DIP-30 to SSOP-30. |
| SOP | CNV-SSOP-PIC16 | 30-pin SOP(PITCH 0.65mm,5.7mm) socket. Supports MICROCHIP PIC16C54,PIC16C55,PIC16C56, PIC16C57,PIC16C58A.(28-pin SSOP) |

| | | |
|-----|------------------|--|
| SOP | CNV-SSOP-Z86E08 | 30-pin SOP(PITCH 0.65mm,5.7mm) socket. Supports ZILOG Z86E02 1925,Z86E08 186X.(20-pin SSOP) |
| SOP | CNV-TSOP-31LF041 | 40-pin SOP(PITCH 0.5mm,12.4mm) socket. Supports SST 31LF041.(40-pin TSOP) |
| SOP | CNV-TSOP-AT45XXD | 28-pin SOP(PITCH 0.55mm,11.8mm) socket. Supports ATMEL AT45DB161D.(28-pin TSOP) |
| SOP | CNV-TSOP-DIP40B | 40-pin SOP(PITCH 0.5mm,18.5mm) socket. Supports SST SST49LF016C. |
| SOP | CNV-TSOP-DIP40C | 40-pin SOP(PITCH 0.5mm,18.5mm) socket. Supports pin to pin,DIP-40 to TSOP-40. |
| SOP | CNV-TSOP-EP1M32 | 32-pin SOP(PITCH 0.5mm,18.5mm) socket. Supports all 32-pin TSOP EEPROM from 1MB up. AMD 29F010,29F040; CATALYST 28F010; HITACHI 28F010,29C101,28F4001; MITSUBISHI M5M28F101VP/RV. (32-pin TSOP,8x20mm) |
| SOP | CNV-TSOP-EP1M32B | 32-pin SOP(PITCH 0.5mm,11.8mm) socket. Supports SHARP LHF00L19.(32-pin TSOP) |

| | | |
|-----|------------------|---|
| SOP | CNV-TSOP-EP1M32C | 32-pin SOP(PITCH 0.5mm,12mm) socket. Supports all 32-pin TSOP EEPROM from 1MB up. (32-pin TSOP,8x14mm) |
| SOP | CNV-TSOP-EP1M32R | 32-pin SOP(PITCH 0.5mm,18.5mm) socket. Supports EEPROM 1Mbits.(byte wide reverse)(32-pin TSOP) |
| SOP | CNV-TSOP-EP1M40G | 40-pin SOP(PITCH 0.5mm,12.4mm) socket. Supports ATMEL 27C1024.(40-pin TSOP) |
| SOP | CNV-TSOP-EP1M40I | 40-pin SOP(PITCH 0.5mm,12.4mm) socket. Supports WINBOND W29C102.(40-pin TSOP) |
| SOP | CNV-TSOP-EP1M40J | 40-pin SOP(PITCH 0.5mm,12.4mm) socket. Supports STM M29W102BB/BT.(40-pin TSOP) |
| SOP | CNV-TSOP-EP512 | 28-pin SOP(PITCH 0.55mm,11.8mm) socket. Supports ATMEL 28C16-T,28C64,28C64B,28C256, 29C256,27C256R,27C512R; MITSUBISHI 28C64A; STM M27C256B,M27C512,M27V512.(28-pin TSOP) |
| SOP | CNV-TSS56-COP8X9 | 56-pin SOP(PITCH 0.5mm,6.1mm) socket. Supports NATIONAL COP8CB/CC/CDR9,COP8SB/SC/SDR9. (56-pin TSSOP) |

| | | |
|-----|-------------------|--|
| SOP | CNV-TSSOP-27C520 | 20-pin SOP(PITCH 0.65mm,4.6mm) socket. Supports ATMEL AT27C520,AT27LV520.(20-pin TSSOP) |
| SOP | CNV-TSSOP-89LPC | 28-pin SOP(PITCH 0.65mm,4.4mm) socket. NXP P89LPC9301,P89LPC931A1,P89LPC9331, P89LPC9341.(28-pin TSSOP) |
| SOP | CNV-TSSOP-8XC5XX2 | 38-pin SOP(PITCH 0.5mm,4.4mm) socket. Supports PHILIPS 87C54X2.(38-pin TSSOP) |
| SOP | CNV-TSSOP-AT25XX | 20-pin SOP(PITCH 0.65mm,4.6mm) socket. Supports ATMEL AT25128,AT25256.(20-pin TSSOP) |
| SOP | CNV-TSSOP-DIP16 | 16-pin SOP(PITCH 0.65mm,4.4mm) socket. Supports pin to pin,DIP-16 to TSSOP-16. |
| SOP | CNV-TSSOP-DIP20 | 20-pin SOP(PITCH 0.65mm,4.6mm) socket. Supports pin to pin,DIP-20 to TSSOP-20. |
| SOP | CNV-TSSOP-DIP24 | 24-pin SOP(PITCH 0.65mm,4.4mm) socket. Supports ATMEL ATF16V8B/BQ/BL/BQL, ATF22V10B/BQ/BL/BQL.(24-pin TSSOP) |
| SOP | CNV-TSSOP-DIP28 | 28-pin SOP(PITCH 0.65mm,4.4mm) socket. Supports pin to pin,DIP-28 to TSSOP-28. |

| | | |
|-----|-------------------|---|
| SOP | CNV-TSSOP-DIP8A | 16-pin SOP(PITCH 0.65mm,4.4mm) socket. Supports XICOR X25057.(8-pin TSSOP) |
| SOP | CNV-TSSOP-LPC76X | 20-pin SOP(PITCH 0.65mm,4.4mm) socket. Supports NXP,PHILIPS P87LPC762.(20-pin TSSOP) |
| SOP | CNV-TSSOP-X25330 | 16-pin SOP(PITCH 0.65mm,4.4mm) socket. Supports XICOR X25330.(14-pin TSSOP) |
| SOT | CNV-DS2502-SOT23 | 3-pin SOT(PITCH 0.95mm,1.3mm) socket. Supports DALLAS DS2502.(3-pin SOT-23) |
| SOT | CNV-SOT-PIC10F20X | 6-pin SOT(PITCH 0.95mm,1.63mm) socket. Supports MICROCHIP PIC10F200,PIC10F202,PIC10F204, PIC10F206.(6-pin SOT-23) |