

Mini Magnetic Stripe Card Reader

(Model No.: CR1300-U)

Features:

- Compatible with Android System.
- All 3 tracks can set to 75/210 BPI;
- USB interface.
- Long service life (500,000 card passes).
- Suitable for all ISO7811/7812, ANSI, AAMVA and CA DMV magnetic cards.



Specifications:

Dimension	90mm(L) x 26mm(W) x 28mm(H)		
Weight	85g(approx.)		
Power Supply	+5V DV ±5%		
Power consumption	40mA (max.)		
Operation Locus	Indoor use		
Card Standard	ISO7811/7812		
Track Position	ISO 1 (IATA)	ISO 2 (ABA)	ISO 3 (MINTS)
Recording Density	210 BPI	75 BPI	210 BPI
Recording Capacity	79 Characters (7bits)	40 Characters (5bits)	107 Characters (5bits)
Interface	USB		
Card Thickness	Plastic 0.76 ± 0.08mm		
Head Function	Read only 1.5mm		
Operation Speed	10 ~ 150cm/sec		
Life of Head	500,000 card passes (1 pass : one swipe)		
Error Rate	Less than 0.5% (JSE Test card)		
Temperature	Storage : -30°C to +70°C Operating : -20°C to +70°C		
Humidity	Storage : 0% to 95% RH Operating : 20% to 90% RH		

Product specifications are subject to change without prior notice.

OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: ocom@ocominc.com;

Tel/Fax: +86.755.8605.3207;



RS232 Magnetic Card Reader Tools V102

Com port: COM1 Baudrate: 9600 [Open Port] [Search port]

SS_ES option: Enable all

Track1 SS % Track2 SS : Track2 SS +
Track1 ES ? Track2 ES ? Track2 ES ?

Track and buzzer option: Track1 enable, Track2 enable, Track3 enable, Buzzer enable

CR option: Track1 CR, Track2 CR, Track3 CR, End of Pact CR

RS232 port option: DTR, RTS, Baudrate: 9600, [Baudrate Setting]

Prefix_suffix option of data packets: Prefix string (Max 30 chars), Suffix string (Max 30 chars)

Power supply options: Normal power supply (Current is larger than 200 ma), Steal power from RS232 Port DTR, RTS (Current less than 10 ma)

[Get Version] [Get Pparameters] [Applicate Currtten Setting] [Restore Default Setting]

TXD: [Text input field] [Send]

RXD: [Text input field] Auto clear, HEX Show, [Clear]

Status

Product specifications are subject to change without prior notice.

Together We Quest For The Best