

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in writing. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、商标、名称权、商号权、域名权、其他知识产权等权利外，本公司保留对涉及发明、实用新型、外观设计、发明专利、软件著作权、商标、名称权、商号权、域名权、其他知识产权等权利的所有权利。

FOR-1755 Rev.1.7

2

3



4

5

6

未注公差/General tolerances(mm)

0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	0.1/10 ±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



4	Cage	Steel	M4/Zn Plated
3	Current carrier	Copper	Sn Plated
2	Screw	Steel	M4/Zn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/50	600/50	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	1000/41	1000/41	1000/41
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8	8	6
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M4, 1.54/14		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	22~8 / 0.5~6		
间距/Pitch(mm)/线数范围/Poles	8/01P		
剥线长度/Stripping length(mm)	10~12		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
颜色说明	11: Grey		

		MATERIAL: /		SURFACE/COLOR: /		
		MAT NO./REV: /		MAT STATUS: /		
APPD: 彭敏	2022.10.27	NAME				
CHKD: 高卫国	2022.10.27	DC6-01P-11-00A&Z(H)				
DRFT: 谢晓栋	2022.10.27	DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
 A4		/	CUSTOMER DRAWING	已发布	1:1	1/1

00	/	NEW DRAWING	谢晓栋	2022.10.27
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6