

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交寄本文件的内容。侵犯者将承担赔偿责任。 本公司保留对涉及发明、实用新型和外观设计的所有权利。

FOR-1754 Rev.1.2

2

3



4

5


6




未注公差/General tolerances(mm)										0.1/10 ±2'
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~400
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.60
UL 标准/UL Standard:										B
额定电压/电流/Rated Voltage(V)/Current(A)										/
IEC 标准/IEC Standard:										C
过压类别/Overvoltage Category/污染等级/Pollution Degree										III/3
额定电压/电流/Rated Voltage(V)/Current(A)										/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)										/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)										26~12/0.2~2.5,4(Sol)
间距/Pitch(mm)/线数范围/Poles										5.2/01P
剥线长度/Stripping length(mm)										10~12
使用温度范围/Operating temperature(°C)										-40~+105
符合RoHS环保要求/Conform to RoHS										Yes



5	Grounding	Copper alloy	Sn plated
4	Current carrier	Copper	Sn plated
3	Spring	Stainless steel	
2	Button	PA66+GF%	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES



T1	20210035	Stuctural change	HuangSh	2021.04.31
REV	ECN	DESCRIPTION	DRFT	DATE

MATERIAL: /		SURFACE: /	
MAT NO.:		 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS: /			
APPD: Li GL 2021.06.10		NAME: DS2.5-QU-PE-01P-1C-00A&Z(H)	
CHKD: Mao J 2021.06.10			
DRFT:HuangSh 2020.07.04		DRAWING NO.: DS2.5-QU-PE-C01	
		REV T1	
SIZE: A4		TYPE: CUSTOMER DRAWING	SCALE: 1.5:1
		SHEET	1/1